

Florida Department of Environmental Protection

Bob Martinez Center 2600 Blair Stone Road Tallahassee, Florida 32399-2400 Charlie Crist Governor

Jeff Kottkamp Lt. Governor

Mimi A. Drew Secretary

NOTICE OF PERMIT

CERTIFIED MAIL
In the Matter of an
Application for Permit by:

Gulf Power Company James O. Vick One Energy Place Pensacola, FL 32520-1 File Number FL0002283-004-IW1S
Jackson County
Gulf Power Company – Scholz Electric Generating Plant

Enclosed is Permit Number FL0002283 to operate the Scholz Electric Generating Plant, issued under Chapter 403, Florida Statutes.

Monitoring requirements under this permit are effective on the first day of the second month following permit issuance. Until such time, the permittee shall continue to monitor and report in accordance with previously effective permit requirements, if any.

Any party to this order (permit) has the right to seek judicial review of the permit action under Section 120.68, Florida Statutes, by the filing of a notice of appeal under Rules 9.110 and 9.190, Florida Rules of Appellate Procedure, with the Clerk of the Department of Environmental Protection, Office of General Counsel, 3900 Commonwealth Boulevard, Mail Station 35, Tallahassee, Florida 32399-3000, and by filing a copy of the notice of appeal accompanied by the applicable filing fees with the appropriate district court of appeal. The notice of appeal must be filed within 30 days from the date when this document is filed with the Clerk of the Department.

Executed in Tallahassee, Florida.

STATE OF FLORIDA DEPARTMENT OF ENVIRONMENTAL PROTECTION

anet G. Llewellyn

Director

Division of Water Resources Management

2600 Blair Stone Road

Tallahassee, Florida 32399-2400

(850) 245-8335

FILING AND ACKNOWLEDGMENT

FILED, on this date, under Section 120.52, Florida Statutes, with the designated Deputy Clerk, receipt of which is hereby acknowledged.

Shields 09-24-10
[Clerk Date]

CERTIFICATE OF SERVICE

The undersigned hereby certifies that this INTENT TO ISSUE and all copies were mailed before the close of business on 09-24-10 to the listed persons.

S. Shields

09-24-10

Name

Date

Enclosure

Certified copies furnished to:

Mark Nuhfer, NPDES Permitting Section, EPA Region 4, Atlanta, GA Susan Kennedy, Q.E.P., Gulf Power Company Mike Markey, Gulf Power Company

Copies furnished by intradepartmental mail to:

Mike Halpin, P.E., DEP Tallahassee Justin Wolfe, Esq., DEP Tallahassee Bill Armstrong, P.E., DEP Pensacola

STATE OF FLORIDA INDUSTRIAL WASTEWATER FACILITY PERMIT

PERMITTEE:

Gulf Power Company

PERMIT NUMBER:

FL0002283-004 (Major)

FILE NUMBER: ISSUANCE DATE:

FL0002283-004-IW1S September 23, 2010

EXPIRATION DATE:

September 22, 2015

RESPONSIBLE OFFICIAL:

James O. Vick One Energy Place Pensacola, Florida 32520 (850) 444-6429

FACILITY:

Scholz Electric Generating Plant 1460 Gulf Power Road Sneads, FL 32460 Jackson County

Latitude: 30° 40' 11.55" N

Longitude: 84° 53' 15.76" W

This permit is issued under the provisions of Chapter 403, Florida Statutes (F.S.), and applicable rules of the Florida Administrative Code (F.A.C.) and constitutes authorization to discharge to waters of the state under the National Pollutant Discharge Elimination System. This permit does not constitute authorization to discharge wastewater other than as expressly stated in this permit. The above named permittee is hereby authorized to operate the facilities in accordance with the documents attached hereto and specifically described as follows:

FACILITY DESCRIPTION:

This facility consists of two coal fired steam electric generating units (Units 1 and 2) with a total nameplate rating of 80 megawatts (MW), and a gross generation capacity of 98 MW.

WASTEWATER TREATMENT:

Non-contact once-through condenser cooling water (OTCW) discharges with chlorination to the on-site discharge canal, and thence to the Apalachicola River, a Class III fresh water. All other industrial and domestic wastewater streams discharge into the on-site ash pond. Discharges to the on-site ash pond consist of low volume wastes (LVW) (i.e. ash sluice water, water softener regeneration wastewater, boiler blowdown and air preheater wash), auxiliary equipment cooling water, coal pile runoff, yard sump runoff, and treated domestic wastewater. Domestic wastewater receives secondary treatment in a package treatment plant prior to discharging to the ash pond. Overflow from the ash pond discharges to the on-site discharge canal, and thence to the Apalachicola River.

REUSE OR DISPOSAL:

Surface Water Discharge D-001: An existing 129.6 MGD maximum permitted discharge to Apalachicola River, Class III Fresh Waters, (WBID# 375G). The point of discharge is located approximately at latitude 30°39' 59" N, longitude 84°53' 12" W.

Internal Outfall I-012: An existing permitted discharge to the discharge canal from the ash pond.

Internal Outfall I-013: An existing permitted discharge to the on-site ash pond.

IN ACCORDANCE WITH: The limitations, monitoring requirements and other conditions set forth in this Cover Sheet and Part I through Part IX on pages 1 through 24 of this permit.

Gulf Power Comp.

FACILITY: Scholz Elec

Scholz Electric Generating Plant

PERMIT N BER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

I. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

A. Surface Water Discharges

1. During the period beginning on the issuance date and lasting through the expiration date of this permit, the permittee is authorized to discharge once-through non-contact cooling water and ash pond overflow from Outfall D-001(COMBINED PLANT DISCHARGE) to Apalachicola River. Such discharge shall be limited and monitored by the permittee as specified below and reported in accordance with Permit Condition I.C.3.:

			Efflu	ent Limitations	Monitor	ring Requirem	ents	
Parameter	Units	Max/ Min	Limit	Statistical Basis	Frequency of Analysis	Sample Type	Monitoring Site Number	Notes
Flow	MGD	Max	Report	Daily Maximum	Daily; 24 hours	Calculated	Calculated EFF-2	
Temperature (F), Water (Intake)	Deg F	Max Max	Report Report	Daily Maximum Monthly Average	4 Days/Week	Meter	INT-1	
Temperature (F), Water (Discharge)	Deg F	Max Max	Report Report	Daily Maximum Monthly Average	4 Days/Week	Meter	EFF-1	See I.A.6
рН	s.u.	Min Max	6.0 8.5	Daily Minimum Daily Maximum	Weekly	Grab	EFF-2	See I.A.12
Oil and Grease	mg/L	Max Max	5.0 5.0	Daily Maximum Monthly Average	Quarterly	Grab	EFF-2	
Chlorine, Total Residual	mg/L	Max Max	0.01 0.01	Daily Maximum Monthly Average	Weekly	Multiple Grabs ¹	EFF-2	See I.A.7
Chlorination Duration	min	Max	120	Daily Maximum	Weekly	Calculated	EFF-2	
Copper, Total Recoverable	ug/L	Max		Single Sample	Annually	24-hr TPC	EFF-2, INT-1	See I.A.4 and I.A.5
Cadmium, Total Recoverable	ug/L	Max		Single Sample	Annually	24-hr TPC	EFF-2, INT-1	See I.A.4 and I.A.5
Lead, Total Recoverable	ug/L	Max		Single Sample	Annually	24-hr TPC	EFF-2, INT-1	See I.A.4 and I.A.5
Iron, Total Recoverable	mg/L	Max Max	1.0 1.0	Daily Maximum Monthly Average	Annually	24-hr TPC	EFF-2, INT-1	See I.A.5
Mercury, Total Recoverable	ug/L	Max	Report	Daily Maximum	Annually	24-hr TPC	EFF-2, INT-1	
Hardness, Total (as CaCO3)	mg/L	Max	Report	Single Sample	Annually	24-hr TPC	EFF-2	See I.A.4
Nitrogen, Ammonia, Total (as N)	mg/L	Max	Report	Single Sample	Quarterly	Grab	EFF-2	See I.A.12
Nitrogen, Kjeldahl, Total (as N)	mg/L	Max	Report	Single Sample	Quarterly	Grab	EFF-2	See I.A.12
Nitrite plus Nitrate, Total 1 det. (as N)	mg/L	Max	Report	Single Sample	Quarterly	Grab	EFF-2	See I.A.12
Nitrogen, Total	mg/L	Max	Report	Single Sample	Quarterly	Grab	EFF-2	See I.A.12
Phosphorus, Total (as P)	mg/L	Max	Report	Single Sample	Quarterly	Grab	EFF-2	See I.A.12
Phosphate, Ortho (as PO4)	mg/L	Max	Report	Single Sample	Quarterly	Grab	EFF-2	See I.A.12
Chronic Whole Effluent Toxicity, 7-Day IC25 (Ceriodaphnia dubia)	percent	Min	100	Single Sample	Quarterly ²	24-hr TPC	EFF-2	See I.A.13

¹ Multiple grabs for TRC shall consist of grab samples collected at approximately the beginning of the period of expected chlorine discharge and once every 15 minutes thereafter until the end of the period of chlorine discharge.

Whole effluent toxicity testing shall be completed during the period of chlorination of the once-through cooling water.

PERMITTEE: FACILITY:

Gulf Power Comp.

Scholz Electric Generating Plant

PERMIT 1. .ABER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

			Efflu	ent Limitations	Monito	ring Requirem	ents	
Parameter	Units	Max/ Min	Limit	Statistical Basis	Frequency of Analysis	Sample Type	Monitoring Site Number	Notes
Chronic Whole Effluent Toxicity, 7-Day IC25 (Pimephales promelas)	percent	Min	100	Single Sample	Quarterly ²	24-hr TPC	EFF-2	See I.A.13

2. Effluent samples shall be taken at the monitoring site locations listed in Permit Condition I.A.1. and as described below:

Monitoring Site Number	Description of Monitoring Site
EFF-2	In the discharge canal 200 feet downstream from the ash pond discharge prior to the confluence of the discharge canal and the Apalachicola River.
INT-1	At the condenser inlet.
EFF-1	At condenser outlet.

- 3. The discharge shall not contain components that settle to form putrescent deposits or float as debris, scum, oil, or other matter. [62-302.500(1)(a)]
- 4. The limit for "Copper, Total Recoverable, Cadmium, Total Recoverable, and Lead, Total Recoverable" shall be calculated using the following equation(s):

$$\begin{split} Cu &\leq e^{(0.8545[\ln H]-1.702)} \\ Cd &\leq e^{(0.7409[\ln H]-4.719)} \\ Pb &\leq e^{(1.273[\ln H]-4.705)} \end{split}$$

Total hardness shall be measured at the time of the effluent sample. The "ln H" means the natural logarithm of total hardness expressed as mg/L of $CaCO_3$. For metals criteria involving equations with hardness, the hardness shall be set at 25 mg/L if actual hardness is <25 mg/L and set at 400 mg/L if actual hardness is >400 mg/L.

The measured effluent value shall be recorded on the DMR in the parameter row for "Copper, Total Recoverable, Cadmium, Total Recoverable, and Lead, Total Recoverable (effluent)." The calculated effluent limit shall be recorded on the DMR in the parameter row for "Copper, Total Recoverable, Cadmium, Total Recoverable, and Lead, Total Recoverable (calculated limit)." Compliance with the effluent limitation is determined by calculating the difference between the measured effluent value and the calculated. The compliance value shall be recorded on the DMR in the parameter row for "Copper, Total Recoverable, Cadmium, Total Recoverable, and Lead, Total Recoverable (effluent minus calculated limit)." The compliance value shall not exceed 0.00. [62-302.530(23), 62-302.530(15), and 62-302.530(39)]

- 5. The actual limit shall be the water quality standard set in Rule 62-302.530, F.A.C., for Class III fresh water or the concentration of the intake cooling water, whichever is greater. If the outfall D-001 composite sample exceeds the intake concentration, and the intake concentration exceeds the water quality standard, a minimum of five (5) additional sub-samples shall be measured from the original intake and outfall composites and a "student t-test" shall be run on these additional sub-sample comparing discharge concentrations with intake concentrations; unless the discharge concentration exceeds the intake concentration at the 95% confidence level, the facility shall be in compliance with the limit.
- 6. Discharge from Outfall D-001 is subject to the requirements of Rule 62-302.520(1), F.A.C.
- 7. Limitations and monitoring requirements for total residual chlorine are not applicable for time periods in which once-through condenser cooling water is not chlorinated.

Gulf Power Comp.

FACILITY:

Scholz Electric Generating Plant

PERMIT N BER: EXPIRATION DATE:

FL0002283-004 (Major)

September 22, 2015

8. Discharge of uncontaminated stormwater; intake screen backwash water, turbine oil cooling water, and hydrogen cooler water is permitted without limitations or monitoring requirements except that there shall be no discharge of floating oil.

- 9. The permittee shall maintain the current intake through-screen velocity such that the existing maximum velocity is not exceeded. [C.W.A. 316(b)]
- 10. The permittee shall maintain current traveling screen practices at Units 1 and 2 so as to assure that the screens are cycled twice during each 24 hours of continuous operation unless precluded by repair/maintenance requirements. [C.W.A. 316(b)]
- 11. The permittee shall develop a plan in accordance with the schedule in Condition VII.3 to help return live fish, shellfish, and other aquatic organisms collected or trapped on the intake screens to their natural habitat. Other material shall be removed from the intake screens and disposed of in accordance with all existing Federal, State and/or Local laws and regulations that apply to waste disposal. Such material shall not be returned to the receiving waters. [C.W.A. 316(b)]
- 12. After 24 months of monitoring for nutrients, the permittee may request through a permit revision for a reduction of the monitoring requirement.
- 13. The permittee shall comply with the following requirements to evaluate chronic whole effluent toxicity of the discharge from outfall D-001.
 - a. Effluent Limitation
 - (1) In any routine or additional follow-up test for chronic whole effluent toxicity, the 25 percent inhibition concentration (IC25) shall not be less than 100% effluent. [Rules 62-302.530(61) and 62-4.241(1)(b), F.A.C.]
 - (2) For acute whole effluent toxicity, the 96-hour LC50 shall not be less than 100% effluent in any test. [Rules 62-302.500(1)(a)4. and 62-4.241(1)(a), F.A.C.]
 - b. Monitoring Frequency
 - (1) Routine toxicity tests shall be conducted once every three months, the first starting within 60 days of the issuance date of this permit and lasting for the duration of this permit.
 - (2) Upon completion of four consecutive, valid routine tests that demonstrate compliance with the effluent limitation in 13.a.(1) above, the permittee may submit a written request to the Department for a reduction in monitoring frequency to once every six months. The request shall include a summary of the data and the complete bioassay laboratory reports for each test used to demonstrate compliance. The Department shall act on the request within 45 days of receipt. Reductions in monitoring shall only become effective upon the Department's written confirmation that the facility has completed four consecutive valid routine tests that demonstrate compliance with the effluent limitation in 13.a.(1) above.
 - (3) If a test within the sequence of the four is deemed invalid based on the acceptance criteria in EPA-821-R-02-013, but is replaced by a repeat valid test initiated within 21 days after the last day of the invalid test, the invalid test will not be counted against the requirement for four consecutive valid tests for the purpose of evaluating the reduction of monitoring frequency.
 - c. Sampling Requirements
 - (1) For each routine test or additional follow-up test conducted, a total of three 24-hour composite samples of final effluent shall be collected and used in accordance with the sampling protocol discussed in EPA-821-R-02-013, Section 8.
 - (2) The first sample shall be used to initiate the test. The remaining two samples shall be collected according to the protocol and used as renewal solutions on Day 3 (48 hours) and Day 5 (96 hours) of the test
 - (3) Samples for routine and additional follow-up tests shall not be collected on the same day.
 - d. Test Requirements
 - (1) Routine Tests: All routine tests shall be conducted using a control (0% effluent) and a minimum of five test dilutions: 100%, 50%, 25%, 12.5%, and 6.25% final effluent.

PERMITTEE: FACILITY:

Gulf Power Compa

Scholz Electric Generating Plant

PERMIT N .BER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

(2) The permittee shall conduct a daphnid, Ceriodaphnia dubia, Survival and Reproduction Test and a fathead minnow, Pimephales promelas, Larval Survival and Growth Test, concurrently.

- (3) All test species, procedures and quality assurance criteria used shall be in accordance with Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Freshwater Organisms, 4th Edition, EPA-821-R-02-013. Any deviation of the bioassay procedures outlined herein shall be submitted in writing to the Department for review and approval prior to use. In the event the above method is revised, the permittee shall conduct chronic toxicity testing in accordance with the revised method.
- (4) The control water and dilution water shall be moderately hard water as described in EPA-821-R-02-013, Section 7.2.3.

e. Quality Assurance Requirements

- (1) A standard reference toxicant (SRT) quality assurance (QA) chronic toxicity test shall be conducted with each species used in the required toxicity tests either concurrently or initiated no more than 30 days before the date of each routine or additional follow-up test conducted. Additionally, the SRT test must be conducted concurrently if the test organisms are obtained from outside the test laboratory unless the test organism supplier provides control chart data from at least the last five monthly chronic toxicity tests using the same reference toxicant and test conditions. If the organism supplier provides the required SRT data, the organism supplier's SRT data and the test laboratory's monthly SRT-QA data shall be included in the reports for each companion routine or additional follow-up test required.
- (2) If the mortality in the control (0% effluent) exceeds 20% for either species in any test or does not meet "test acceptability criteria", the test for that species (including the control) shall be invalidated and the test repeated. Test acceptability criteria for each species are defined in EPA-821-R-02-013, Section 13.12 (Ceriodaphnia dubia) and Section 11.11 (Pimephales promelas). The repeat test shall begin within 21 days after the last day of the invalid test.
- (3) If 100% mortality occurs in all effluent concentrations for either test species prior to the end of any test and the control mortality is less than 20% at that time, the test (including the control) for that species shall be terminated with the conclusion that the test fails and constitutes non-compliance.
- (4) Routine and additional follow-up tests shall be evaluated for acceptability based on the observed dose-response relationship as required by EPA-821-R-02-013, Section 10.2.6., and the evaluation shall be included with the bioassay laboratory reports.

f. Reporting Requirements

- (1) Results from all required tests shall be reported on the Discharge Monitoring Report (DMR) as follows:
 - (a) Routine and Additional Follow-up Test Results: The calculated IC25 for each test species shall be entered on the DMR.
- (2) A bioassay laboratory report for each routine test shall be prepared according to EPA-821-R-02-013, Section 10, Report Preparation and Test Review, and mailed to the Department at the address below within 30 days after the last day of the test.
- (3) For additional follow-up tests, a single bioassay laboratory report shall be prepared according to EPA-821-R-02-013, Section 10, and mailed within 30 days after the last day of the second valid additional follow-up test.
- (4) Data for invalid tests shall be included in the bioassay laboratory report for the repeat test.
- (5) The same bioassay data shall not be reported as the results of more than one test.
- (6) All bioassay laboratory reports shall be sent to:

Florida Department of Environmental Protection

Northwest District Office

160 Governmental Center

Pensacola, Florida 32502-5794

g. Test Failures

- (1) A test fails when the test results do not meet the limits in 13.a.(1).
- (2) Additional Follow-up Tests:
 - (a) If a routine test does not meet the chronic toxicity limitation in 13.a.(1) above, the permittee shall notify the Department at the address above within 21 days after the last day of the failed routine test and conduct two additional follow-up tests on each species that failed the test in accordance with 13.d.

PERMITTEE: FACILITY:

Gulf Power Comp

Scholz Electric Generating Plant

PERMIT 1 BER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

(b) The first test shall be initiated within 28 days after the last day of the failed routine test. The remaining additional follow-up tests shall be conducted weekly thereafter until a total of two valid additional follow-up tests are completed.

- (c) The first additional follow-up test shall be conducted using a control (0% effluent) and a minimum of five dilutions: 100%, 50%, 25%, 12.5%, and 6.25% effluent. The permittee may modify the dilution series in the second additional follow-up test to more accurately bracket the toxicity such that at least two dilutions above and two dilutions below the target concentration and a control (0% effluent) are run. All test results shall be analyzed according to the procedures in EPA-821-R-02-013.
- (3) In the event of three valid test failures (whether routine or additional follow-up tests) within a 12-month period, the permittee shall notify the Department within 21 days after the last day of the third test failure.
 - (a) The permittee shall submit a plan for correction of the effluent toxicity within 60 days after the last day of the third test failure.
 - (b) The Department shall review and approve the plan before initiation.
 - (c) The plan shall be initiated within 30 days following the Department's written approval of the plan.
 - (d) Progress reports shall be submitted quarterly to the Department at the address above.
 - (e) During the implementation of the plan, the permittee shall conduct quarterly routine whole effluent toxicity tests in accordance with 13.d. Additional follow-up tests are not required while the plan is in progress. Following completion or termination of the plan, the frequency of monitoring for routine and additional follow-up tests shall return to the schedule established in 13.b.(1). If a routine test is invalid according to the acceptance criteria in EPA-821-R-02-013, a repeat test shall be initiated within 21 days after the last day of the invalid routine test.
 - (f) Upon completion of four consecutive quarterly valid routine tests that demonstrate compliance with the effluent limitation in 13.a.(1) above, the permittee may submit a written request to the Department to terminate the plan. The plan shall be terminated upon written verification by the Department that the facility has passed at least four consecutive quarterly valid routine whole effluent toxicity tests. If a test within the sequence of the four is deemed invalid, but is replaced by a repeat valid test initiated within 21 days after the last day of the invalid test, the invalid test will not be counted against the requirement for four consecutive quarterly valid routine tests for the purpose of terminating the plan.
- (4) If chronic toxicity test results indicate greater than 50% mortality within 96 hours in an effluent concentration equal to or less than the effluent concentration specified as the acute toxicity limit in 13.(a)(2), the Department may revise this permit to require acute definitive whole effluent toxicity testing.
- (5) The additional follow-up testing and the plan do not preclude the Department taking enforcement action for acute or chronic whole effluent toxicity failures.

[62-4.241, 62-620.620(3)]

B. Internal Outfalls

1. During the period beginning on the issuance date and lasting through the expiration date of this permit, the permittee is authorized to discharge low volume wastes, auxiliary equipment cooling water, coal pile runoff, yard sump runoff, and treated domestic wastewater from I-012 (ASH POND DISCHARGE) to discharge canal. Such discharge shall be limited and monitored by the permittee as specified below and reported in accordance with Permit Condition I.C.3.:

			Et	ffluent Limitations	Monito	oring Requirem	ents	
Parameter	Units	Max/ Min	Limit	Statistical Basis	Frequency of Analysis	Sample Type	Monitoring Site Number	Notes
Flow	MGD	Max	Report	Daily Average	Weekly	Calculated	OUI-3	
Solids, Total Suspended	mg/L	Max Max	30 100	Monthly Average Daily Maximum	Weekly	24-hr TPC	OUI-3	

Gulf Power Compa

FACILITY:

Scholz Electric Generating Plant

PERMIT N .BER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

			E1	ffluent Limitations	Monito	ring Requirem	ents	
Parameter	Units	Max/ Min	Limit	Statistical Basis	Frequency of Analysis	Sample Type	Monitoring Site Number	Notes
Oil and Grease	mg/L	Max Max	15 20	Monthly Average Daily Maximum	Bi-weekly; every 2 weeks	Grab	OUI-3	
pН	s.u.	Min Max	6.0 9.0	Daily Minimum Daily Maximum	Weekly	Grab	OUI-3	
Nickel, Total Recoverable	ug/L	Max	Report	Instantaneous Maximum	Annually	Grab	OUI-3	

2. Effluent samples shall be taken at the monitoring site locations listed in Permit Condition I.B.1. and as described below:

Monitoring Site Number	Description of Monitoring Site
OUI-3	The point of discharge at the ash pond discharge weir.

3. During the period beginning on the issuance date and lasting through the expiration date of this permit, the permittee is authorized to discharge domestic treatment plant wastewater from I-013 (DOMESTIC WASTEWATER TREATMENT PLANT EFFLUENT) to the ash pond. Such discharge shall be limited and monitored by the permittee as specified below and reported in accordance with Permit Condition I.C.3.:

	i.		Efflu	ent Limitations	Moni	toring Requirer	nents	
Parameter	Units	Max/ Min	Limit	Statistical Basis	Frequency of Analysis	Sample Type	Monitoring Site Number	Notes
Flow	MGD	Max Max	Report Report	Daily Maximum Monthly Average	Weekly	Meter	OUI-4	
Biochemical Oxygen Demand-5	mg/L	Max Max	30.0 60.0	Monthly Average Daily Maximum	Quarterly	Grab	OUI-4	
Solids, Total Suspended	mg/L	Max Max	30.0 60.0	Monthly Average Daily Maximum	Quarterly	Grab	OUI-4	
Coliform, Fecal	#/100mL	Max		See I.B.6	Quarterly	Grab	OUI-4	See I.B.6

4. Effluent samples shall be taken at the monitoring site locations listed in Permit Condition I.B.3. and as described below:

Monitoring Site Number	Description of Monitoring Site
OUI-4	The point of discharge at the wastewater treatment outlet box.

- 5. Wastewater treatment plant effluent shall be continuously chlorinated and 0.5 mg/l chlorine residual shall be maintained in the contact chamber for 15 minutes prior to discharge.
- 6. The arithmetic mean of the monthly fecal coliform values collected during an annual period, as described in subparagraph 62-600.740(1)(a)1., F.A.C., shall not exceed 200 per 100 mL of reclaimed water sample. The geometric mean of the fecal coliform values for a minimum of 10 samples of reclaimed water, each collected on a separate day during a period of 30 consecutive days (monthly), shall not exceed 200 per 100 mL of sample. No more than 10 percent of the samples collected (the 90th percentile) during a period of 30 consecutive days shall exceed 400 fecal Coliform values per 100 mL of sample. Any one sample shall not exceed 800 fecal coliform values per 100 mL of sample. *Note:* To report the value of the sample that corresponds to the 90th percentile value, list the fecal Coliform values obtained during the month in ascending order. Report the value of the sample that corresponds to the 90th percentile (multiply the number of samples by 0.9). For example, for 30 samples, report the corresponding fecal number for the 27th value of ascending order.

PERMITTEE: FACILITY:

Gulf Power Comp

Scholz Electric Generating Plant

PERMIT N BER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

[62-600.440(4)(c)]

C. Other Limitations and Monitoring and Reporting Requirements

- 1. The sample collection, analytical test methods, and method detection limits (MDLs) applicable to this permit shall be conducted using a sufficiently sensitive method to ensure compliance with applicable water quality standards and effluent limitations and shall be in accordance with Rule 62-4.246, Chapters 62-160 and 62-601, F.A.C., and 40 CFR 136, as appropriate. The list of Department established analytical methods, and corresponding MDLs (method detection limits) and PQLs (practical quantitation limits), which is titled "FAC 62-4 MDL/PQL Table (April 26, 2006)" is available at http://www.dep.state.fl.us/labs/library/index.htm. The MDLs and PQLs as described in this list shall constitute the minimum acceptable MDL/PQL values and the Department shall not accept results for which the laboratory's MDLs or PQLs are greater than those described above unless alternate MDLs and/or PQLs have been specifically approved by the Department for this permit. Any method included in the list may be used for reporting as long as it meets the following requirements:
 - a. The laboratory's reported MDL and PQL values for the particular method must be equal or less than the corresponding method values specified in the Department's approved MDL and PQL list;
 - b. The laboratory reported MDL for the specific parameter is less than or equal to the permit limit or the applicable water quality criteria, if any, stated in Chapter 62-302, F.A.C. Parameters that are listed as "report only" in the permit shall use methods that provide an MDL, which is equal to or less than the applicable water quality criteria stated in 62-302, F.A.C.; and
 - c. If the MDLs for all methods available in the approved list are above the stated permit limit or applicable water quality criteria for that parameter, then the method with the lowest stated MDL shall be used.

When the analytical results are below method detection or practical quantification limits, the permittee shall report the actual laboratory MDL and/or PQL values for the analyses that were performed following the instructions on the applicable discharge monitoring report.

Where necessary, the permittee may request approval of alternate methods or for alternative MDLs or PQLs for any approved analytical method. Approval of alternate laboratory MDLs or PQLs are not necessary if the laboratory reported MDLs and PQLs are less than or equal to the permit limit or the applicable water quality criteria, if any, stated in Chapter 62-302, F.A.C. Approval of an analytical method not included in the above-referenced list is not necessary if the analytical method is approved in accordance with 40 CFR 136 or deemed acceptable by the Department. [62-4.246, 62-160]

- 2. The permittee shall provide safe access points for obtaining representative influent and effluent samples which are required by this permit. [62-620.320(6)]
- 3. Monitoring requirements under this permit are effective on the first day of the second month following permit issuance. Until such time, the permittee shall continue to monitor and report in accordance with previously effective permit requirements, if any. During the period of operation authorized by this permit, the permittee shall complete and submit to the Department Discharge Monitoring Reports (DMRs) in accordance with the frequencies specified by the REPORT type (i.e. monthly, toxicity, quarterly, semiannual, annual, etc.) indicated on the DMR forms attached to this permit. Monitoring results for each monitoring period shall be submitted in accordance with the associated DMR due dates below.

REPORT Type on DMR	Monitoring Period	Due Date
Monthly	first day of month - last day of month	28 th day of following month
Quarterly	January 1 - March 31	April 28
	April 1 - June 30	July 28
	July 1 - September 30	October 28
	October 1 - December 31	January 28
Semiannual	January 1 - June 30	July 28
	July 1 - December 30	January 28
Annual	January 1 - December 31	January 28

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

DMRs shall be submitted for each required monitoring period including months of no discharge. The permittee shall make copies of the attached DMR form(s) and shall submit the completed DMR form(s) to the Department by the twenty-eighth (28th) of the month following the month of operation at the address specified below:

Florida Department of Environmental Protection Wastewater Compliance Evaluation Section, Mail Station 3551 Bob Martinez Center 2600 Blair Stone Road Tallahassee, Florida 32399-2400

[62-620.610(18)]

4. Unless specified otherwise in this permit, all reports and other information required by this permit, including 24-hour notifications, shall be submitted to or reported to, as appropriate, the Department's Northwest District Office at the address specified below:

Florida Department of Environmental Protection Northwest District Office 160 Governmental Center Pensacola, Florida 32502-5794

Phone Number - (850) 595-8300 FAX Number - (850) 595-8417 (All FAX copies shall be followed by original copies.)

[62-620.305]

- 5. All reports and other information shall be signed in accordance with the requirements of Rule 62-620.305, F.A.C. [62-620.305]
- 6. If there is no discharge from the facility on a day when the facility would normally sample, the sample shall be collected on the day of the next discharge. [62-620.320(6)]
- 7. Any bypass of the treatment facility which is not included in the monitoring specified in Sections I.A and I.B., is to be monitored for flow and all other required parameters. For parameters other than flow, at least one grab sample per day shall be monitored. Daily flow shall be monitored or estimated, as appropriate, to obtain reportable data. All monitoring results shall be reported on the appropriate DMR.
- 8. There shall be no discharge of polychlorinated biphenyl compounds. [40 CFR Part 423.12(b)(2)]
- 9. Discharge of any product registered under the Federal Insecticide, Fungicide, and Rodenticide Act to any waste stream which ultimately may be released to waters of the State is prohibited unless specifically authorized elsewhere in this permit. This requirement is not applicable to products used for lawn and agricultural purposes or to the use of herbicides if used in accordance with labeled instructions and any applicable State permit. A permit revision from the Department shall be required prior to the use of any biocide or chemical additive used in the cooling system (except chlorine as authorized elsewhere in this permit) or any other portion of the treatment system which may be toxic to aquatic life. The permit revision request shall include:
 - a. Name and general composition of biocide or chemical
 - b. Frequencies of use
 - c. Quantities to be used
 - d. Proposed effluent concentrations
 - e. Acute and/or chronic toxicity data (laboratory reports shall be prepared according to Section 12 of EPA document no. EPA-821-R-02-012 EP entitled, Methods for Measuring the Acute Toxicity of Effluents and Receiving Waters for Freshwater and Marine Organisms, or most current addition.)
 - f. Product data sheet

PERMITTEE: FACILITY:

Gulf Power Company

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

g. Product label

The Department shall review the above information to determine if a major or minor permit revision is necessary. Discharge associated with the use of such biocide or chemical is not authorized without a permit revision by the Department. Permit revisions shall be processed in accordance with the requirements of Chapter 62-620, F.A.C.

- 10. Discharge of any waste resulting from the combustion of toxic, hazardous, or metal cleaning wastes to any waste stream which ultimately discharges to waters of the State is prohibited, unless specifically authorized elsewhere in this permit. The discharge of plant ash transport water, resulting from the combustion of onspecification used oil as authorized under the Resource Conservation and Recovery Act and 40 CFR Part 266, via the ash pond shall be an authorized discharge of this permit.
- 11. Metals concentrations shall be reported and expressed as the total recoverable fraction. [62-302.500(2)(d) and 62-620.620(2)(c)1, F.A.C.]
- 12. The permittee shall not store coal, soil, or other similar erodable materials in a manner in which runoff is uncontrolled, or conduct construction activities in a manner which produces uncontrolled runoff.
- 13. The permittee is authorized to use the following chemicals and biocides in the Units 1 and 2 cooling water systems and other wastewater streams:

Chemical Name	System Used
Ammonium Hydroxide	Boiler Water System
Hydrazine	Boiler Water System
Calcium hypochlorite	Once-through cooling water system

II. SLUDGE AND RESIDUALS MANAGEMENT REQUIREMENTS

A. Domestic Residuals Management Requirements

- 1. The method of residuals use or disposal by this facility is transport to a residuals management facility (RMF). Transportation of the residuals to an alternative RMF does not require a permit modification. However, use of an alternative RMF requires the submittal of a copy of the agreement pursuant to Rule 62-640.880(1)(c), F.A.C., along with a written notification to the Department at least 30 days before transport of the residuals. [62-620.320(6), 62-640.880(1)]
- 2. The permittee shall be responsible for proper management or disposal of its residuals. [62-640.300(5)]
- 3. The permittee shall not be held responsible for treatment, management, use, or land application violations that occur after its residuals have been accepted by a permitted RMF which the source facility has an agreement with in accordance with Rule 62-640.880(1)(c), F.A.C., for further treatment, management, use or land application. [62-640.300(5)]
- 4. Disposal of residuals, septage, and other solids in a solid waste landfill, or disposal by placement on land for purposes other than soil conditioning or fertilization, such as at a monofill, surface impoundment, waste pile, or dedicated site, shall be in accordance with Chapter 62-701, F.A.C. [62-640.100(6)(k)] & 4]
- 5. The permittee shall keep hauling records to track the transport of its residuals to the RMF. The hauling records shall contain the following information:

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

Residuals Management Facility

- 1. Date and Time Received
- 2. Amount of Residuals Received
- 3. Name and ID Number of Source Facility
- 4. Signature of Hauler
- Signature of Responsible Party at Residuals Management Facility

Source Facility

Date and Time Shipped

Amount of Residuals Shipped
 Degree of Treatment (if applicable)

4. Name and ID Number of Residuals

Management Facility or Treatment Facility

Signature of Responsible Party at Source Facility

6. Signature of Hauler and Name of Hauling Firm

These records shall be kept for five years and shall be made available for inspection upon request by the Department. A copy of the hauling records information maintained by the source facility shall be provided upon delivery of the residuals to the residuals management facility or treatment facility. The permittee shall report to the Department within 24 hours of discovery any discrepancy in the quantity of residuals leaving the source facility and arriving at the residuals management facility or treatment facility. [62-640.880(4)]

7. Storage of residuals or other solids at the permitted facility shall require prior written notification to the Department if the storage lasts longer than 30 days. [62-640.300(4)]

B. Industrial Sludge Management Requirements

- 1. The permittee shall be responsible for proper treatment, management, use or land application of its sludges.
- 2. Disposal of sludge in a solid waste management facility permitted by the Department shall be in accordance with the requirements of Chapter 62-701, F.A.C. Storage, transportation, and disposal of sludge/solids characterized as hazardous waste shall be in compliance with requirements of Chapter 62-730, F.A.C.
- 3. The permittee shall keep records of the amount of sludge disposed, transported, or incinerated. If a person other than the permittee is responsible for sludge transporting, disposal, or incineration, the permittee shall also keep the following records:
 - a. Name, address and telephone number of any transporter, and any manifests or bill of lading used;
 - b. Name and location of the site of disposal, treatment or incineration;
 - c. Name, address, and telephone number of the entity responsible for the disposal, treatment, or incineration site.

III. GROUND WATER REQUIREMENTS

- 1. During the period of operation authorized by this permit, the permittee shall sample ground water in accordance with this permit and the approved ground water monitoring plan prepared under 62-520, F.A.C.
- 2. The following monitoring wells shall be sampled for the ground water discharge:

Monitoring	Alternate Well Name and/or Description	Latitude			I	ongitu	de	Depth (Feet)	Aquifer Monitored	New or Existing
Well ID	of Monitoring Location	0 .	ŧ	"	0	1	11	(1 001)	Montorea	2
MWB-205	MW-205MD	30	40	18	84	53	35	-	Floridan	Existing
MWB-2051	MW-205S	30	40	18	84	53	•35	-	Surficial	Existing
MWC-2	WSW-2	30	40	19	84	53	17	-	Floridan	Existing
MWC-203	MW-203MD	30	39	59	84	53	15		Floridan	Existing
MWC-204	MW-204MD	30	39	57	84	53	28	-	Floridan	Existing
MWC-210	MW-210MD	30	40	6	84	53	14	-	Floridan	Existing
MWC-210	MW-210MD	30	39	55	84	53	22	-	Floridan	Existing
MWC-2031	MW-203S	30	39	59	84	53	15	-	Surficial	Existing
MWI-204S	MWI-204S, Intermediate	30	39	57	84	53	28	-	Surficial	Existing

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

Monitoring Well ID	Alternate Well Name and/or Description of Monitoring Location	I	atitud	е]	Longitu	de	Depth (Feet)	Aquifer Monitored	New or Existing
,,, он 15	or whomen mg Doddion	0	'	,,	0	'	".			
MWI-210S	MWI-210S,Intermediate	30	40	6	84	53	14	-	Surficial	Existing
MWP-103	MW-103; Monitoring Piezometer well.	30	39	-59	84	53	15	-	Floridan	Existing
MWP-105	MW-105; Monitoring Piezometer well.	30	40	17	84	53	35	-	Floridan	Existing
MWP-110	MW-110A; Monitoring Piezometer well.	30	40	7	84	53	13	-	Floridan	Existing
MWP-112	MW-112; Monitoring Piezometer well.	30	39	55	84	53	22	-	Floridan	Existing

MWC = Compliance; MWB = Background; MWI = Intermediate; MWP = Piezometer

[62-520.600]

3. The following parameters shall be analyzed for each monitoring well identified in Permit Condition III.2. Results shall be reported on the permittee's Discharge Monitoring Report in accordance with Condition I.C.3.:

Parameter	Compliance Well Limit	Units	Sample Type	Monitoring Frequency
Water Level Relative to NGVD	Report	ft	In Situ	Annually
pН	Report	s.u.	Grab	Annually
Specific Conductance	Report	umhos/cm	Grab	Annually
Aluminum, Total Recoverable	Report	mg/L	Grab	Annually
Arsenic, Total Recoverable	Report	mg/L	Grab	Annually
Cadmium, Total Recoverable	0.005	mg/L	Grab	Annually
Chloride (as Cl)	Report	mg/L	Grab	Annually
Chromium, Total Recoverable	0.100	mg/L	Grab	Annually
Iron, Total Recoverable	Report	mg/L	Grab	Annually
Lead, Total Recoverable	0.015	mg/L	Grab	Annually
Magnesium, Total Recoverable	Report	mg/L	Grab	Annually
Mercury, Total Recoverable	0.002	mg/L	Grab	Annually
Selenium, Total Recoverable	0.050	mg/L	Grab	Annually
Sulfate, Total	Report	mg/L	Grab	Annually
Solids, Total Dissolved (TDS)	Report	mg/L	Grab	Annually
Alpha, Gross Particle Activity	15	pCi/L	Grab	Once Every 5 Years
Radium 226 + Radium 228, Total	5	pCi/L	Grab	Once Every 5 Years

For piezometers, monitoring and reporting is required only for water level information.

[62-520.600(11)(b)]

- 4. The zone of discharge for the ash pond shall extend horizontally along the ground surface to the facility's property line and vertically from the land surface to the base of the surficial aquifer. [62-520.200(26)] [62-520.465]
- 5. A complete sampling record shall be provided for each monitoring well. This record shall include water level, total depth of the well, volume of water in the well, volume of water removed, stabilization documentation including pH, conductivity, and temperature; time interval of purging; time sample is taken; and device(s) used for purging (including discharge rate) and sampling.
- 6. When Gross Alpha Particle Activity is detected above 5.0 pCi/L, then combined Radium 226 and 228 shall be tested and reported.
- 7. In the event the water quality monitoring shows a violation of the applicable water quality standards, the permittee shall arrange for a confirmation re-sampling within 15 days after the permittee's receipt of laboratory results. In the event that the permittee chooses not to conduct the reconfirmation sampling, the Department shall consider the initial analysis to be representative of the current water quality conditions at this facility. If the initial results demonstrate or the re-sampling confirms ground water contamination, the permittee shall notify the Department in writing within 14 days of this finding.
- 8. The permittee shall develop a written technical report pursuant to the schedule in Condition VI.4 to summarize and interpret the water quality data and water levels obtained from permit issuance to the date of renewal application

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

submittal. The report shall be submitted by a qualified professional and shall contain the following items at a minimum:

- a. Tables and graphs of water quality data, including hydrographs, for all monitoring wells. Rainfall data should be included with the hydrographs.
- b. A comparison of water quality results between background well and downgradient wells.
- c. A summary of all violations of applicable water quality standards.
- d. Ground water contour maps for each sampling event.
- e. A discussion of any data that is thought to be inconsistent or suspect.
- f. A summary of the physical condition of the monitoring system. This should be based on visual observation and sampling records.
- 9. The permittee's discharge to ground water shall not cause a violation of water quality standards for ground waters at the boundary of the zone of discharge, in accordance with Rules 62-520.400 and 62-520.420, F.A.C.
- 10. The ground water minimum criteria specified in Rule 62-520.400 F.A.C., shall be met within the zone of discharge. [62-520.400 and 62-520.420(4)]
- 11. If the concentration for any constituent listed in Condition III.3 in the natural background quality of the ground water is greater than the stated maximum, or in the case of pH is also less than the minimum, the representative background quality shall be the prevailing standard. [62-520.420(2)]
- 12. Water levels shall be recorded before evacuating each well for sample collection. Elevation references shall include the top of the well casing and land surface at each well site (NAVD allowable) at a precision of plus or minus 0.01 foot. [62-520.600(11)(c)]
- 13. Ground water monitoring wells shall be purged prior to sampling to obtain representative samples. [62-160.210]
- 14. Analyses shall be conducted on unfiltered samples, unless filtered samples have been approved by the Department's Northwest District Office as being more representative of ground water conditions. [62-520.310(5)]
- 15. If any monitoring well becomes damaged or inoperable, the permittee shall notify the Department's Northwest District Office immediately and a detailed written report shall follow within seven days. The written report shall detail what problem has occurred and remedial measures that have been taken to prevent recurrence. All monitoring well design and replacement shall be approved by the Department's Northwest District Office prior to installation. [62-520.600][62-620.320(6)]
- 16. All piezometers and monitoring wells not part of the approved ground water monitoring plan are to be plugged and abandoned in accordance with Rule 62-532.500(4), F.A.C., unless future use is intended. [62-532.500(4)]
- 17. The permittee shall provide verbal notice to the Department as soon as practical after discovery of a sinkhole within an area for the management or application of wastewater or sludge. The permittee shall immediately implement measures appropriate to control the entry of contaminants, and shall detail these measures to the Department in a written report within 7 days of the sinkhole discovery.
- 18. Ground water monitoring test results shall be submitted on Part D of Form 62-620.910(10) in accordance with Condition I.C.3. [62-520.600(11)(b)]

IV. ADDITIONAL LAND APPLICATION REQUIREMENTS

1. When the three-month average daily flow for the most recent three consecutive months exceeds 50 percent of the permitted capacity of the treatment plant or reuse and disposal systems, the permittee shall submit to the Department a capacity analysis report. This initial capacity analysis report shall be submitted within 180 days after the last day of the last month of the three-month period referenced above. The capacity analysis report shall be prepared in accordance with Rule 62-600.405, F.A.C. [62-600.405(4)]

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

2. The application to renew this permit shall include a detailed operation and maintenance performance report prepared in accordance with Rule 62-600.735, F.A.C. [62-600.735(1)]

V. OPERATION AND MAINTENANCE REQUIREMENTS

- 1. During the period of operation authorized by this permit, the wastewater facilities shall be operated under the supervision of a person who is qualified by formal training and/or practical experience in the field of water pollution control. [62-620.320(6)]
- 2. The on-site domestic facility shall have a Class D or higher operator 2 visits/week on nonconsecutive days for a total of 1 hour/week. There shall be no more than 5 days between the last visit in one week and the first visit in the next week. The lead/chief operator for the domestic facility must be a Class D operator, or higher.
- 3. The permittee shall maintain the following records and make them available for inspection on the site of the permitted facility.
 - a. Records of all compliance monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, including, if applicable, a copy of the laboratory certification showing the certification number of the laboratory, for at least three years from the date the sample or measurement was taken;
 - b. Copies of all reports required by the permit for at least three years from the date the report was prepared;
 - c. Records of all data, including reports and documents, used to complete the application for the permit for at least three years from the date the application was filed;
 - d. A copy of the current permit;
 - e. A copy of any required record drawings; and
 - f. Copies of the logs and schedules showing plant operations and equipment maintenance for three years from the date of the logs or schedules.

[62-620.350]

VI. SCHEDULES

1. The following improvement actions shall be completed according to the following schedule.

Action Item	Completion Date
Domestic Wastewater Plant Operator Certification	Issuance Date of Permit + 6 months

[62-620.320(6)]

2. The following improvement actions shall be completed according to the following schedule. The Best Management Practices/Pollution Prevention (BMP3) Plan shall be prepared and implemented in accordance with Part VII of this permit.

Action Item	Completion Date
Continue implementing the existing BMP3 Plan	Issuance date of permit

[62-620.320(6)]

3. Within six months of the effective date of this permit, the permittee shall schedule a meeting with the Department to discuss the contents of the aquatic organism return plan in accordance with Condition I.A.11 and shall submit the plan to the Department within 12 months of the effective date of this permit. The plan shall be implemented within 24 months subsequent to approval by the Department.

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

4. When an application for renewal of this permit is submitted, no later than 180 days prior to permit expiration, the permittee shall submit a technical report on groundwater in accordance with the requirements of Condition III.8.

VII.BEST MANAGEMENT PRACTICES/STORMWATER POLLUTION PREVENTION PLANS

1. General Conditions

In accordance with Section 304(e) and 402(a)(2) of the Clean Water Act (CWA) as amended, 33 U.S.C. §§ 1251 et seq., and the Pollution Prevention Act of 1990, 42 U.S.C. §§ 13101-13109, the permittee must develop and implement a plan for utilizing practices incorporating pollution prevention measures. References to be considered in developing the plan are "Criteria and Standards for Best Management Practices Authorized Under Section 304(e) of the Act," found at 40 CFR 122.44 Subpart K and the Storm Water Management Industrial Activities Guidance Manual, EPA/833-R92-002 and other EPA documents relating to Best Management Practice guidance.

a. Definitions

(1) The term "pollutants" refers to conventional, non-conventional and toxic pollutants.

(2) Conventional pollutants are: biochemical oxygen demand (BOD), suspended solids, pH, fecal coliform bacteria and oil & grease.

(3) Non-conventional pollutants are those which are not defined as conventional or toxic.

(4) Toxic pollutants include, but are not limited to: (a) any toxic substance listed in Section 307(a)(1) of the CWA, any hazardous substance listed in Section 311 of the CWA, or chemical listed in Section 313(c) of the Superfund Amendments and Reauthorization Act of 1986; and (b) any substance (that is not also a conventional or non-conventional pollutant except ammonia) for which EPA has published an acute or chronic toxicity criterion.

(5) "Significant Materials" is defined as raw materials; fuels; materials such as solvents and detergents; hazardous substances designated under Section 101(14) of CERCLA; and any chemical the facility is required to report pursuant to EPCRA, Section 313; fertilizers; pesticides; and waste products such as ashes, slag and sludge.

(6) "Pollution prevention" and "waste minimization" refer to the first two categories of EPA's preferred hazardous waste management strategy: first, source reduction and then, recycling.

(7) "Recycle/Reuse" is defined as the minimization of waste generation by recovering and reprocessing usable products that might otherwise become waste; or the reuse or reprocessing of usable waste products in place of the original stock, or for other purposes such as material recovery, material regeneration or energy production.

- (8) "Source reduction" means any practice which: (a) reduces the amount of any pollutant entering a waste stream or otherwise released into the environment (including fugitive emissions) prior to recycling, treatment or disposal; and (b) reduces the hazards to public health and the environment associated with the release of such pollutant. The term includes equipment or technology modifications, process or procedure modifications, reformulation or redesign of products, substitution of raw materials, and improvements in housekeeping, maintenance, training, or inventory control. It does not include any practice which alters the physical, chemical, or biological characteristics or the volume of a pollutant through a process or activity which itself is not integral to, or previously considered necessary for, the production of a product or the providing of a service.
- (9) "BMP3" means a Best Management Practices Pollution Prevention Plan incorporating the requirements of 40 CFR § 125, Subpart K, plus pollution prevention techniques, except where other existing programs are deemed equivalent by the permittee. The permittee shall certify the equivalency of the other referenced programs.

(10) The term "material" refers to chemicals or chemical products used in any plant operation (i.e., caustic soda, hydrazine, degreasing agents, paint solvents, etc.). It does not include lumber, boxes, packing materials, etc.

2. Best Management Practices/Pollution Prevention Plan

The permittee shall develop and implement a BMP3 plan for the facility, which is the source of wastewater and storm water discharges, covered by this permit. The plan shall be directed toward reducing those pollutants of concern which discharge to surface waters and shall be prepared in accordance with good engineering and good housekeeping practices. For the purposes of this permit, pollutants of concern shall be limited to toxic pollutants, as defined above, known to the discharger. The plan shall address all activities which could or do contribute these pollutants to the surface water discharge, including process, treatment, and ancillary activities.

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT No., BER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

a. Signatory Authority & Management Responsibilities

The BMP3 plan shall be signed by permittee or their duly authorized representative in accordance with rule 62-620.305(2)(a) and (b). The BMP3 plan shall be reviewed by plant environmental/engineering staff and plant manager. Where required by Chapter 471-(P.E.) or Chapter 492 (P.G.) Florida Statutes, applicable portions of the BMP3 plant shall be signed and sealed by the professional(s) who prepared them.

A copy of the plant shall be retained at the facility and shall be made available to the permit issuing authority upon request.

The BMP3 plan shall contain a written statement from corporate or plant management indicating management's commitment to the goals of the BMP3 program. Such statements shall be publicized or made known to all facility employees. Management shall also provide training for the individuals responsible for implementing the BMP3 plan.

b. BMP3 Plan Requirements

- (1) Name & description of facility, a map illustrating the location of the facility & adjacent receiving waters, and other maps, plot plans or drawings, as necessary;
- (2) Overall objectives (both short-term and long-term) and scope of the plan, specific reduction goals for pollutants, anticipated dates of achievement of reduction, and a description of means for achieving each reduction goal;
- (3) A description of procedures relative to spill prevention, control & countermeasures and a description of measures employed to prevent storm water contamination;
- (4) A description of practices involving preventive maintenance, housekeeping, recordkeeping, inspections, and plant security; and
- (5) The description of a waste minimization assessment performed in accordance with the conditions outlined in condition c below, results of the assessment, and a schedule for implementation of specific waste reduction practices.

c. Waste Minimization Assessment

The permittee is encouraged but not required to conduct A waste minimization assessment (WMA) for this facility to determine actions that could be taken to reduce waste loading and chemical losses to all wastewater and/or storm water streams as described in Part VII.D.2 of this permit.

If the permittee elects to develop and implement a WMA, information on plan components can be obtained forms the Department's Industrial Wastewater website, or from:

Florida Department of Environmental Protection Industrial Wastewater Section, Mail Station 3545 2600 Blair Stone Road Tallahassee, Florida 32399-2400 (850) 245-8589 (850) 245-8669 – Fax

d. Best Management Practices & Pollution Prevention Committee Recommended:

A Best Management Practices Committee (Committee) should be established to direct or assist in the implementation of the BMP3 plan. The Committee should be comprised of individuals within the plant organization who are responsible for developing the BMP3 plan and assisting the plant manager in its implementation, monitoring of success, and revision. The activities and responsibilities of the Committee should address all aspects of the facility's BMP3 plan. The scope of responsibilities of the Committee should be described in the plan.

e. Employee Training

Employee training programs shall inform personnel at all levels of responsibility of the components & goals of the BMP3 plan and shall describe employee responsibilities for implementing the plan. Training shall address topics such as good housekeeping, materials management, record keeping & reporting, spill prevention & response, as well as specific waste reduction practices to be employed. Training should also disclose how individual employees may contribute suggestions concerning the BMP3 plan or suggestions regarding Pollution Prevention. The plan shall identify periodic dates for such training.

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

f. Plan Development & Implementation

The BMP3 plan shall be developed and implemented 6 months after the effective date of this permit, unless any later dates are specified in this permit. Any portion of the WMA which is ongoing at the time of development or implementation shall be described in the plan. Any waste reduction practice which is recommended for implementation over a period of time shall be identified in the plan, including a schedule for its implementation.

g. Submission of Plan Summary & Progress/Update Reports

- (1) Plan Summary: Not later than 2 years after the effective date of the permit, a summary of the BMP3 plan shall be developed and maintained at the facility and made available to the permit issuing authority upon request. The summary should include the following: a brief description of the plan, its implementation process, schedules for implementing identified waste reduction practices, and a list of all waste reduction practices being employed at the facility. The results of waste minimization assessment studies already completed as well as any scheduled or ongoing WMA studies shall be discussed.
- (2) Progress/Update Reports: Annually thereafter for the duration of the permit progress/update reports documenting implementation of the plan shall be maintained at the facility and made available to the permit issuing authority upon request. The reports shall discuss whether or not implementation schedules were met and revise any schedules, as necessary. The plan shall also be updated as necessary and the attainment or progress made toward specific pollutant reduction targets documented. Results of any ongoing WMA studies as well as any additional schedules for implementation of waste reduction practices shall be included.
- (3) A timetable for the various plan requirements follows:

Timetable for BMP3 Plan Requirements:

REQUIREMENT

TIME FROM EFFECTIVE DATE OF THIS PERMIT

Progress/Update Reports

3 years, and then annually thereafter

The permittee shall maintain the plan and subsequent reports at the facility and shall make the plan available to the Department upon request.

h. Plan Review & Modification

If following review by the Department, the BMP3 plan is determined insufficient, the permittee will be notified that the BMP3 plan does not meet one or more of the minimum requirements of this Part. Upon such notification from the Department, the permittee shall amend the plan and shall submit to the Department a written certification that the requested changes have been made. Unless otherwise provided by the Department, the permittee shall have 30 days after such notification to make the changes necessary.

The permittee shall modify the BMP3 plan whenever there is a change in design, construction, operation, or maintenance, which has a significant effect on the potential for the discharge of pollutants to waters of the State or if the plan proves to be ineffective in achieving the general objectives of reducing pollutants in wastewater or storm water discharges. Modifications to the plan may be reviewed by the Department in the same manner as described above.

VIII. OTHER SPECIFIC CONDITIONS

A. Specific Conditions Applicable to All Permits

- 1. Where required by Chapter 471 or Chapter 492, F.S., applicable portions of reports that must be submitted under this permit shall be signed and sealed by a professional engineer or a professional geologist, as appropriate. [62-620.310(4)]
- 2. Drawings, plans, documents or specifications submitted by the permittee, not attached hereto, but retained on file at the Department's Northwest District Office, are made a part hereof.
- 3. This permit satisfies Industrial Wastewater program permitting requirements only and does not authorize operation of this facility prior to obtaining any other permits required by local, state or federal agencies.
- 4. The permittee shall provide verbal notice to the Department's Northwest District Office as soon as practical after discovery of a sinkhole or other karst feature within an area for the management or application of wastewater, or

PERMITTEE: FACILITY:

Gulf Power Company

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

wastewater sludges. The permittee shall immediately implement measures appropriate to control the entry of contaminants, and shall detail these measures to the Department's Northwest District Office in a written report within 7 days of the sinkhole discovery. [62-620.320(6)]

B. Specific Conditions Related to Existing Manufacturing, Commercial, Mining, and Silviculture Wastewater Facilities or Activities

- 1. Existing manufacturing, commercial, mining, and silvicultural wastewater facilities or activities that discharge into surface waters shall notify the Department as soon as they know or have reason to believe:
 - a. That any activity has occurred or will occur which would result in the discharge, on a routine or frequent basis, of any toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following levels;
 - (1) One hundred micrograms per liter,
 - (2) Two hundred micrograms per liter for acrolein and acrylonitrile; five hundred micrograms per liter for 2, 4-dinitrophenol and for 2-methyl-4, 6-dinitrophenol; and one milligram per liter for antimony, or
 - (3) Five times the maximum concentration value reported for that pollutant in the permit application; or
 - b. That any activity has occurred or will occur which would result in any discharge, on a non-routine or infrequent basis, of a toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following levels;
 - (1) Five hundred micrograms per liter,
 - (2) One milligram per liter for antimony, or
 - (3) Ten times the maximum concentration value reported for that pollutant in the permit application.

[62-620.625(1)]

C. Impoundment Operation and Maintenance

- 1. All ash impoundments used to hold or treat wastewater and other associated wastes shall be operated and maintained to prevent the discharge of pollutants to waters of the State, except as authorized under this permit
- 2. Operation and maintenance of any ash impoundment shall be in accordance with all applicable State regulations. When practicable, piezometers or other instrumentation shall be used as a means to aid monitoring of impoundment integrity.

D. Impoundment Integrity Inspections

- No later than January 31, 2011, and annually thereafter, all impoundments shall be inspected by qualified
 personnel with knowledge and training in impoundment integrity. Annual inspections shall include observations
 of dike and toe areas for erosion, cracks or bulges, seepage, wet or soft soil, changes in geometry, the depth and
 elevation of the impounded water, sediment or slurry, freeboard, changes in vegetation such as overly lush, dead
 or unnaturally tilted vegetation, and any other changes which may indicate a potential compromise to
 impoundment integrity.
- 2. Within 30 days after the annual inspection, a qualified, responsible officer shall certify to the Department that no breaches or structural defects resulting in the discharges to surface waters of the State and that no changes were observed which may indicate a potential compromise to impoundment integrity during the previous calendar year.

The certification shall also include a statement that the ash pond provides the necessary minimum wet weather detention volume to contain the combined volume for all direct rainfall and all rainfall runoff to the pond resulting from the 10-year, 24-hour rainfall event and maximum dry weather plant waste flows which could occur during a 24-hour period.

3. The permittee shall conduct follow-up inspections within 7 days after large or extended rain events (i.e., 25-year, 24-hour precipitation event).

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

4. In the event that the impoundment integrity is compromised and may result in a potential discharge to surfaces waters of the State, the permittee shall notify the Department within twenty-four (24) hours of becoming aware of the situation and provide a proposed course of corrective action and implementation schedule within fifteen (15) days after notifying the Department. Observed changes such as significant increases in seepage or seepage carrying sediment may be signs of imminent impoundment failure and should be addressed immediately.

E. Reporting and Recordkeeping Requirements for Impoundments

- 1. The summarized findings of all monitoring activities, inspections, and corrective actions pertaining to the impoundment integrity, and operation and maintenance of all impoundments shall be documented and kept on-site in accordance with permit Condition V.3, and made available to Department inspectors upon request.
- 2. Starting with the issuance of this permit, all pertinent impoundment permits, design, construction, operation, and maintenance information, including but not limited to: plans, geotechnical and structural integrity studies, copies of permits, associated certifications by qualified, Florida-registered professional engineer, and regulatory approvals, shall be kept on site in accordance with permit Condition V.3 and made available to Department inspectors upon request.

F." Duty to Reapply

- 1. The permittee is not authorized to discharge to waters of the State after the expiration date of this permit, unless:
 - a. the permittee has applied for renewal of this permit at least 180 days before the expiration date (Month, Day, Year) using the appropriate forms listed in Rule 62-620.910, F.A.C., and in the manner established in the Department of Environmental Protection Guide to Permitting Wastewater Facilities or Activities Under Chapter 62-620, F.A.C., including submittal of the appropriate processing fee set forth in Rule 62-4.050, F.A.C.; or
 - b. the permittee has made complete the application for renewal of this permit before the permit expiration date.

[62-620.335(1)-(4), F.A.C.]

- 2. When publishing Notice of Draft and Notice of Intent in accordance with Rules 62-110.106 and 62-620.550, F.A.C., the permittee shall publish the notice at its expense in a newspaper of general circulation in the county or counties in which the activity is to take place either
 - a. Within thirty days after the permittee has received a notice; or
 - b. Within thirty days after final agency action.

Failure to publish a notice is a violation of this permit.

G. Reopener Clauses

- 1. The permit shall be revised, or alternatively, revoked and reissued in accordance with the provisions contained in Rules 62-620.325 and 62-620.345 F.A.C., if applicable, or to comply with any applicable effluent standard or limitation issued or approved under Sections 301(b)(2)(C) and (D), 304(b)(2) and 307(a)(2) of the Clean Water Act (the Act), as amended, if the effluent standards, limitations, or water quality standards so issued or approved:
 - a. Contains different conditions or is otherwise more stringent than any condition in the permit/or;
 - b. Controls any pollutant not addressed in the permit.

The permit as revised or reissued under this paragraph shall contain any other requirements then applicable.

2. The permit may be reopened to adjust effluent limitations or monitoring requirements should future Water Quality Based Effluent Limitation determinations, water quality studies, DEP approved changes in water quality standards, EPA established Total Maximum Daily Loads (TMDLs), or other information show a need for a

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

different limitation, monitoring requirement, or more stringent requirements or any applicable standards pertaining to the operation and maintenance of coal combustion waste impoundments.

- 3. The Department or EPA may develop a TMDL during the life of the permit. Once a TMDL has been established and adopted by rule, the Department shall revise this permit to incorporate the final findings of the TMDL.
- 4. The permit shall be reopened for revision as appropriate to address new information that was not available at the time of this permit issuance or to comply with requirements of new regulations, standards, or judicial decisions relating to CWA 316(b).

IX. GENERAL CONDITIONS

- 1. The terms, conditions, requirements, limitations and restrictions set forth in this permit are binding and enforceable pursuant to Chapter 403, Florida Statutes. Any permit noncompliance constitutes a violation of Chapter 403, Florida Statutes, and is grounds for enforcement action, permit termination, permit revocation and reissuance, or permit revision. [62-620.610(1)]
- 2. This permit is valid only for the specific processes and operations applied for and indicated in the approved drawings or exhibits. Any unauthorized deviations from the approved drawings, exhibits, specifications or conditions of this permit constitutes grounds for revocation and enforcement action by the Department. [62-620.610(2)]
- 3. As provided in subsection 403.087(7), F.S., the issuance of this permit does not convey any vested rights or any exclusive privileges. Neither does it authorize any injury to public or private property or any invasion of personal rights, nor authorize any infringement of federal, state, or local laws or regulations. This permit is not a waiver of or approval of any other Department permit or authorization that may be required for other aspects of the total project which are not addressed in this permit. [62-620.610(3)]
- 4. This permit conveys no title to land or water, does not constitute state recognition or acknowledgment of title, and does not constitute authority for the use of submerged lands unless herein provided and the necessary title or leasehold interests have been obtained from the State. Only the Trustees of the Internal Improvement Trust Fund may express State opinion as to title. [62-620.610(4)]
- 5. This permit does not relieve the permittee from liability and penalties for harm or injury to human health or welfare, animal or plant life, or property caused by the construction or operation of this permitted source; nor does it allow the permittee to cause pollution in contravention of Florida Statutes and Department rules, unless specifically authorized by an order from the Department. The permittee shall take all reasonable steps to minimize or prevent any discharge, reuse of reclaimed water, or residuals use or disposal in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. [62-620.610(5)]
- 6. If the permittee wishes to continue an activity regulated by this permit after its expiration date, the permittee shall apply for and obtain a new permit. [62-620.610(6)]
- 7. The permittee shall at all times properly operate and maintain the facility and systems of treatment and control, and related appurtenances, that are installed and used by the permittee to achieve compliance with the conditions of this permit. This provision includes the operation of backup or auxiliary facilities or similar systems when necessary to maintain or achieve compliance with the conditions of the permit. [62-620.610(7)]
- 8. This permit may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit revision, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [62-620.610(8)]
- 9. The permittee, by accepting this permit, specifically agrees to allow authorized Department personnel, including an authorized representative of the Department and authorized EPA personnel, when applicable, upon presentation of

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

credentials or other documents as may be required by law, and at reasonable times, depending upon the nature of the concern being investigated, to:

- a. Enter upon the permittee's premises where a regulated facility, system, or activity is located or conducted, or where records shall be kept under the conditions of this permit;
- b. Have access to and copy any records that shall be kept under the conditions of this permit;
- c. Inspect the facilities, equipment, practices, or operations regulated or required under this permit; and
- d. Sample or monitor any substances or parameters at any location necessary to assure compliance with this permit or Department rules.

[62-620.610(9)]

- 10. In accepting this permit, the permittee understands and agrees that all records, notes, monitoring data, and other information relating to the construction or operation of this permitted source which are submitted to the Department may be used by the Department as evidence in any enforcement case involving the permitted source arising under the Florida Statutes or Department rules, except as such use is proscribed by Section 403.111, F.S., or Rule 62-620.302, F.A.C. Such evidence shall only be used to the extent that it is consistent with the Florida Rules of Civil Procedure and applicable evidentiary rules. [62-620.610(10)]
- 11. When requested by the Department, the permittee shall within a reasonable time provide any information required by law which is needed to determine whether there is cause for revising, revoking and reissuing, or terminating this permit, or to determine compliance with the permit. The permittee shall also provide to the Department upon request copies of records required by this permit to be kept. If the permittee becomes aware of relevant facts that were not submitted or were incorrect in the permit application or in any report to the Department, such facts or information shall be promptly submitted or corrections promptly reported to the Department. [62-620.610(11)]
- 12. Unless specifically stated otherwise in Department rules, the permittee, in accepting this permit, agrees to comply with changes in Department rules and Florida Statutes after a reasonable time for compliance; provided, however, the permittee does not waive any other rights granted by Florida Statutes or Department rules. A reasonable time for compliance with a new or amended surface water quality standard, other than those standards addressed in Rule 62-302.500, F.A.C., shall include a reasonable time to obtain or be denied a mixing zone for the new or amended standard. [62-620.610(12)]
- 13. The permittee, in accepting this permit, agrees to pay the applicable regulatory program and surveillance fee in accordance with Rule 62-4.052, F.A.C. [62-620.610(13)]
- 14. This permit is transferable only upon Department approval in accordance with Rule 62-620.340, F.A.C. The permittee shall be liable for any noncompliance of the permitted activity until the transfer is approved by the Department. [62-620.610(14)]
- 15. The permittee shall give the Department written notice at least 60 days before inactivation or abandonment of a wastewater facility or activity and shall specify what steps will be taken to safeguard public health and safety during and following inactivation or abandonment. [62-620.610(15)]
- 16. The permittee shall apply for a revision to the Department permit in accordance with Rules 62-620.300, F.A.C., and the Department of Environmental Protection Guide to Permitting Wastewater Facilities or Activities Under Chapter 62-620, F.A.C., at least 90 days before construction of any planned substantial modifications to the permitted facility is to commence or with Rule 62-620.325(2), F.A.C., for minor modifications to the permitted facility. A revised permit shall be obtained before construction begins except as provided in Rule 62-620.300, F.A.C. [62-620.610(16)]
- 17. The permittee shall give advance notice to the Department of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements. The permittee shall be responsible for any and all damages which may result from the changes and may be subject to enforcement action by the Department for penalties or revocation of this permit. The notice shall include the following information:
 - a. A description of the anticipated noncompliance;

Gulf Power Company

FACILITY:

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

b. The period of the anticipated noncompliance, including dates and times; and

c. Steps being taken to prevent future occurrence of the noncompliance.

[62-620.610(17)]

- 18. Sampling and monitoring data shall be collected and analyzed in accordance with Rule 62-4.246 and Chapters 62-160, 62-601, and 62-610, F.A.C., and 40 CFR 136, as appropriate.
 - a. Monitoring results shall be reported at the intervals specified elsewhere in this permit and shall be reported on a Discharge Monitoring Report (DMR), DEP Form 62-620.910(10), or as specified elsewhere in the permit.
 - b. If the permittee monitors any contaminant more frequently than required by the permit, using Department approved test procedures, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR.
 - c. Calculations for all limitations which require averaging of measurements shall use an arithmetic mean unless otherwise specified in this permit.
 - d. Except as specifically provided in Rule 62-160.300, F.A.C., any laboratory test required by this permit shall be performed by a laboratory that has been certified by the Department of Health Environmental Laboratory Certification Program (DOH ELCP). Such certification shall be for the matrix, test method and analyte(s) being measured to comply with this permit. For domestic wastewater facilities, testing for parameters listed in Rule 62-160.300(4), F.A.C., shall be conducted under the direction of a certified operator.
 - e. Field activities including on-site tests and sample collection shall follow the applicable standard operating procedures described in DEP-SOP-001/01 adopted by reference in Chapter 62-160, F.A.C.
 - f. Alternate field procedures and laboratory methods may be used where they have been approved in accordance with Rules 62-160.220, and 62-160.330, F.A.C.

[62-620.610(18)]

- 19. Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule detailed elsewhere in this permit shall be submitted no later than 14 days following each schedule date. [62-620.610(19)]
- 20. The permittee shall report to the Department's Northwest District Office any noncompliance which may endanger health or the environment. Any information shall be provided orally within 24 hours from the time the permittee becomes aware of the circumstances. A written submission shall also be provided within five days of the time the permittee becomes aware of the circumstances. The written submission shall contain: a description of the noncompliance and its cause; the period of noncompliance including exact dates and time, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance.
 - a. The following shall be included as information which must be reported within 24 hours under this condition:
 - (1) Any unanticipated bypass which causes any reclaimed water or effluent to exceed any permit limitation or results in an unpermitted discharge,
 - (2) Any upset which causes any reclaimed water or the effluent to exceed any limitation in the permit,
 - (3) Violation of a maximum daily discharge limitation for any of the pollutants specifically listed in the permit for such notice, and
 - (4) Any unauthorized discharge to surface or ground waters.
 - b. Oral reports as required by this subsection shall be provided as follows:
 - (1) For unauthorized releases or spills of treated or untreated wastewater reported pursuant to subparagraph (a)4. that are in excess of 1,000 gallons per incident, or where information indicates that public health or the environment will be endangered, oral reports shall be provided to the STATE WARNING POINT TOLL FREE NUMBER (800) 320-0519, as soon as practical, but no later than 24 hours from the time the permittee becomes aware of the discharge. The permittee, to the extent known, shall provide the following information to the State Warning Point:
 - (a) Name, address, and telephone number of person reporting;
 - (b) Name, address, and telephone number of permittee or responsible person for the discharge;

PERMITTEE: FACILITY:

Gulf Power Company

Scholz Electric Generating Plant

PERMIT NUMBER: EXPIRATION DATE:

FL0002283-004 (Major) September 22, 2015

(c) Date and time of the discharge and status of discharge (ongoing or ceased);

- (d) Characteristics of the wastewater spilled or released (untreated or treated, industrial or domestic wastewater);
- (e) Estimated amount of the discharge;
- (f) Location or address of the discharge;
- (g) Source and cause of the discharge;
- (h) Whether the discharge was contained on-site, and cleanup actions taken to date;
- (i) Description of area affected by the discharge, including name of water body affected, if any; and

(j) Other persons or agencies contacted.

- (2) Oral reports, not otherwise required to be provided pursuant to subparagraph b.1 above, shall be provided to the Department's Northwest District Office within 24 hours from the time the permittee becomes aware of the circumstances.
- c. If the oral report has been received within 24 hours, the noncompliance has been corrected, and the noncompliance did not endanger health or the environment, the Department's Northwest District Office shall waive the written report.

[62-620.610(20)]

21. The permittee shall report all instances of noncompliance not reported under Permit Conditions IX. 17, 18 or 19 of this permit at the time monitoring reports are submitted. This report shall contain the same information required by Permit Condition IX.20 of this permit. [62-620.610(21)]

22. Bypass Provisions.

- a. "Bypass" means the intentional diversion of waste streams from any portion of a treatment works.
- b. Bypass is prohibited, and the Department may take enforcement action against a permittee for bypass, unless the permittee affirmatively demonstrates that:
 - (1) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage; and
 - (2) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and
 - (3) The permittee submitted notices as required under Permit Condition IX. 22. b. of this permit.
- c. If the permittee knows in advance of the need for a bypass, it shall submit prior notice to the Department, if possible at least 10 days before the date of the bypass. The permittee shall submit notice of an unanticipated bypass within 24 hours of learning about the bypass as required in Permit Condition IX. 20. of this permit. A notice shall include a description of the bypass and its cause; the period of the bypass, including exact dates and times; if the bypass has not been corrected, the anticipated time it is expected to continue; and the steps taken or planned to reduce, eliminate, and prevent recurrence of the bypass.
- d. The Department shall approve an anticipated bypass, after considering its adverse effect, if the permittee demonstrates that it will meet the three conditions listed in Permit Condition IX. 22. a. 1 through 3 of this permit.
- e. A permittee may allow any bypass to occur which does not cause reclaimed water or effluent limitations to be exceeded if it is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of Permit Condition IX. 22. a. through c. of this permit.

[62-620.610(22)]

23. Upset Provisions.

- a. "Upset" means an exceptional incident in which there is unintentional and temporary noncompliance with technology-based effluent limitations because of factors beyond the reasonable control of the permittee.
 - (1) An upset does not include noncompliance caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventive maintenance, careless or improper operation.
 - (2) An upset constitutes an affirmative defense to an action brought for noncompliance with technology based permit effluent limitations if the requirements of upset provisions of Rule 62-620.610, F.A.C., are met.

- b. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed contemporaneous operating logs, or other relevant evidence that:
 - (1) An upset occurred and that the permittee can identify the cause(s) of the upset;
 - (2) The permitted facility was at the time being properly operated;
 - (3) The permittee submitted notice of the upset as required in Permit Condition IX.5. of this permit, and
 - (4) The permittee complied with any remedial measures required under Permit Condition IX. 5. of this permit.
- c. In any enforcement proceeding, the burden of proof for establishing the occurrence of an upset rests with the permittee.
- d. Before an enforcement proceeding is instituted, no representation made during the Department review of a claim that noncompliance was caused by an upset is final agency action subject to judicial review.

[62-620.610(23)]

Executed in Tallahassee, Florida.

STATE OF FLORIDA DEPARTMENTOF ENVIRONMENTAL PROTECTION

Janet G. Llewellyn

Director

Division of Water Resource Management

2600 Blair Stone Road

Tallahassee, Florida 32399-2400

(850) 245-8336

Attachment(s):

Discharge Monitoring Report

When Completed mail th	is report to: Department of Environmental Protecti	ion, Wastewater Compliance Evaluation Section, MS 3551, 20	600 Blair Stone Road, Tallahasse	ee, FL 32399-2400	
PERMITTEE NAME:	Gulf Power Company	PERMIT NUMBER:	FL0002283-004-IW1S		
MAILING ADDRESS:	One Energy Place Pensacola, Florida 32520	LIMIT: CLASS SIZE:	Final MA	REPORT FREQUENCY: PROGRAM:	Monthly Industrial
FACILITY: LOCATION:	Scholz Electric Generating Plant 1460 Gulf Power Road Sneads, FL 32460	MONITORING GROUP NUMBER: MONITORING GROUP DESCRIPTION: RE-SUBMITTED DMR: NO DISCHARGE FROM SITE:	D-001 Combined Plant Discharge (C	once-through cooling water and a	ash pond discharge)
COUNTY:	Jackson .	MONITORING PERIOD From:	To:	Southern Management of the Administration of	

Parameter		Quantity (or Loading	Units	Quality or Concentration		Units	No. Ex.	Frequency of Analysis	Sample Type	
Flow	Sample Measurement									Daily; 24 hours	Calculated
ARM Code 50050 1 Mon. Site No. EFF-2	Permit Requirement		Report (Day Max.)	MGD						Dairy, 24 nours	Curporate
Temperature (F), Water Intake) PARM Code 00011 7 Mon. Site No. INT-1	Sample Measurement Permit Requirement					Report (Mo Avg.)	Report (Day Max.)	Deg F		4 Days/Week	Meter
Temperature (F), Water (Discharge) PARM Code 00011 Q Mon. Site No. EFF-1	Sample Measurement Permit Requirement					Report (Mo Avg.)	Report (Day.Max.)	Deg F		4 Days/Week	Meter
pH	Sample Measurement									Weekly	Grab
PARM Code 00400 1 Mon. Site No. EFF-2	Permit Requirement				6.0 (Day Min.)		8.5 (Day Max.)	s.u.		Woekly	- Oraco
Chlorine, Total Residual	Sample Measurement					0.011	0.01	mg/L		Weekly	Grab
PARM Code 50060 1 Mon. Site No. EFF-2	Permit Requirement	100		100		(Mo.Avg.)	(Day Max.)				
Chlorination Duration PARM Code 78739 1 Mon. Site No. EFF-2	Sample Measurement Permit Requirement						120 (Day.Max.)	IBIO		Weekly	Calculated

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

NAME/TITLE OF FRINCII AL EXECUTIVE OFFICER CHARACTERS			
NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	TELEPHONE NO	DATE (mm/dd/yyyy)
	•		TO LOTE (/11/

COMMENT AND EXPLANATION OF ANY VIOLATIONS (Reference all attachments here):

Northwest District Branch (Panama City)

OFFICE:

Limitations and monitoring requirements for total residual chlorine are not applicable for time periods in which once-through condenser cooling water is not chlorinated.

When Completed mail this report to: Department of Environmental Protection, Wastewater Compliance Evaluation Section, MS 3551, 2600 Blair Stone Road, Tallahassee, FL 32399-2400 FL0002283-004-IW1S PERMIT NUMBER: PERMITTEE NAME: Gulf Power Company One Energy Place MAILING ADDRESS: REPORT FREQUENCY: Quarterly Final Pensacola, Florida 32520 LIMIT: Industrial PROGRAM: MA CLASS SIZE: MONITORING GROUP NUMBER: D-001 Scholz Electric Generating Plant FACILITY: Combined Plant Discharge (Once-through cooling water and ash pond discharge) MONITORING GROUP DESCRIPTION: 1460 Gulf Power Road LOCATION: RE-SUBMITTED DMR: Sneads, FL 32460 NO DISCHARGE FROM SITE:

COUNTY: Jackson OFFICE: Northwest	District Branch (Panam	na City)	Mo	ONITORING P	ERIOD Fro	om:	To:				
Parameter		Quantity o	r Loading	Units		Quality or Concentration	ion	Units	No. Ex.	Frequency of Analysis	Sample Type
Oil and Grease	Sample Measurement					5.0	5.0	mg/L		Quarterly	Grab
PARM Code 00556 1 Mon. Site No. EFF-2	Permit Requirement					(Mo.Avg.)	(Day Max.)				
Nitrogen, Ammonia, Total (as N)	Sample Measurement						Passart	mg/L		Quarterly	Grab
PARM Code 00610 1 Mon. Site No. EFF-2	Permit Requirement		11.00				Report (Max.)	ing L		Quarter 1	
Nitrogen, Kjeldahl, Total (as N)	Sample Measurement									Quarterly	Grab
PARM Code 00625 1 Mon. Site No. EFF-2	Permit Requirement						Report (Max.)	mg/L		Quarterry	l Gran
Nitrite plus Nitrate, Total 1 det. (as N)	Sample Measurement							17		Quarterly	Grab
PARM Code 00630 1 Mon. Site No. EFF-2	Permit Requirement					Action of the second of	Report (Max.)	mg/L		Quarterry	Grav

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Knowledge and benefit true, accorded, and complete. Tall true and according to	SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	TELEPHONE NO	DATE (mm/dd/yyyy)
NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	SIGNATURE OF TRIBUTE EXECUTIVE OF THE SIGNATURE OF TRIBUTE EXECUTIVE OF THE SIGNATURE OF TH		
			Í
	,		<u>L</u>

COMMENT AND EXPLANATION OF ANY VIOLATIONS (Reference all attachments here):

Sample Measurement

Permit

Sample

Permit

Sample

Permit

Requirement

Measurement

Requirement

Measurement

Requirement

mg/L

mg/L

mg/L

Report

(Max.)

Report

(Max.)

Report

(Max.)

Grab

Grab

Grab

Quarterly

Quarterly

Quarterly

Nitrogen, Total

PARM Code 00600 1

Phosphorus, Total (as P)

PARM Code 00665 1

PARM Code 00660 1

Mon. Site No. EFF-2

Phosphate, Ortho (as PO4)

Mon. Site No. EFF-2

Mon Site No EFF-2

DISCHARGE MONITORING REPORT - PART A (Continued)

FACILITY:

Scholz Electric Generating Plant

MONITORING GROUP

D-001

FL0002283-004-IW1S

NUMBER: MONITORING PERIOD

From: _____ To: ____

Parameter	Parameter Quantity or Loading Units		Q	uality or Concentr	Units 1		Frequency of Analysis	Sample Type		
7-DAY CHRONIC STATRE Ceriodaphnia dubia(Routine)	Sample Measurement						- areast		Quarterly	24-hr TPC
PARM Code TRP3B P Mon. Site No. EFF-2	Permit Requirement			100 (Min)			percent		Quarterly	24-m 11 C
7-DAY CHRONIC STATRE Ceriodaphnia dubia(Additional)	Sample Measurement									As required by
PARM Code TRP3B Q Mon. Site No. EFF-2	Permit Reguirement		540	100 (Min.)			percent		As needed	the permit
7-DAY CHRONIC STATRE Ceriodaphnia dubia(Additional)	Sample Measurement									
PARM Code TRP3B R Mon. Site No. EFF-2	Permit Requirement	The State of		100 (Min.)			percent		As needed	As required by the permit
7-DAY CHRONIC STATRE Pimephales promelas(Routine)	Sample Measurement			700			percent		Quarterly	24-hr TPC
PARM Code TRP6C P Mon Site No EFF-2	Permit Requirement			100 (Min)			Percent		Agray (e.i.)	
7-DAY CHRONIC STATRE Pimephales promelas(Additional)	Sample Measurement						percent		As needed	As required by
PARM Code TRP6C Q Mon Site No. EFF-2	Permit Requirement			100 (Min.)			porton		713 Heeded	the permit
7-DAY CHRONIC STATRE Pimephales promelas(Additional)	Sample Measurement						percent		As needed	As required by
PARM Code TRP6C R Mon. Site No. EFF-2	Permit Requirement			100 (Min)			person		7 IJ Rosson	the permit
Section 1							and the			
			Section Section	er folkstere i seene	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2				1900 page 300 504 200	
			1000							

^{*}ENTER "MNR" IN THE RESULTS COLUMN FOR EACH TEST THAT IS NOT REQUIRED.

When Completed mail this report to: Department of Environmental Protection, Wastewater Compliance Evaluation Section, MS 3551, 2600 Blair Stone Road, Tallahassee, FL 32399-2400 FL0002283-004-IW1S PERMIT NUMBER: PERMITTEE NAME: Gulf Power Company MAILING ADDRESS: One Energy Place REPORT FREQUENCY: Annually Pensacola, Florida 32520 LIMIT: Final Industrial PROGRAM: MA CLASS SIZE: D-001 MONITORING GROUP NUMBER: Scholz Electric Generating Plant FACILITY: Combined Plant Discharge (Once-through cooling water and ash pond discharge) MONITORING GROUP DESCRIPTION: 1460 Gulf Power Road LOCATION: RE-SUBMITTED DMR: Sneads, FL 32460 NO DISCHARGE FROM SITE:

From:

MONITORING PERIOD

Parameter		Quantity or Loading	Units	Quality or Concentration	Units	No. Ex.	Frequency of Analysis	Sample Type
Copper, Total Recoverable (Intake)	Sample Measurement				ug/L		Annually	24-hr TPC
PARM Code 01119 S Mon. Site No. INT-1	Permit Requirement			Report (Max.)	ug/L		Amuany	27 11 11 0
Copper, Total Recoverable (effluent)	Sample Measurement			Donort	ug/L		Annually	24-hr TPC
PARM Code 01119 1 Mon. Site No. EFF-2	Permit Requirement			Report (Max.)	ug/D		runnany	21.11.17.0
Copper, Total Recoverable (calculated limit)	Sample Measurement			2	ug/L		Annually	Calculated
PARM Code 01119 Q Mon Site No EFF-2	Permit Requirement			Report ² (Max.)	ug/G		1	
Copper, Total Recoverable (effluent minus calculated limit)	Sample Measurement			0.0	ug/L		Annually	Čalculated
PARM Code 01119 R Mon. Site No. EFF-2	Permit Requirement			(Max.)	ug/L		Annually	Carrana
Cadmium, Total Recoverable (Intake)	Sample Measurement				ug/L		Annually	24-hr TPC
PARM Code 01113 S Mon. Site No. INT-1	Permit Requirement			Report (Max.)	Hg/L		runtuany	Z. m H C
Cadmium, Total Recoverable (effluent)	Sample Measurement				8		Angually	24-hr TPC
PARM Code 01113 1	Permit Requirement			Report (Max.)	ng/L		Annually	Z4*(II 17C

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	TELEPHONE NO	DATE (mm/dd/yyyy)
NAMESTITES OF FRINCE AS EXCEPTION			
		<u> </u>	

COMMENT AND EXPLANATION OF ANY VIOLATIONS (Reference all attachments here):

Jackson

Northwest District Branch (Panama City)

COUNTY:

OFFICE:

² See Permit Conditions I.A.4 & I.A.5. If the concentration of the intake is greater than the limit calculated in Condition I.A.4, the intake concentration should be used as the effluent limit.

DISCHARGE MONITORING REPORT - PART A (Continued)

FACILITY:

Scholz Electric Generating Plant

MONITORING GROUP NUMBER:

D-001

PERMIT NUMBER: FL0002283-004-IW1S

NUMBER.			
MONITORING PERIOD	From:	 Го:	***************************************

Parameter		Quantity or Loading		Units		Quali	ty or Concentrati	on	Units	No. Ex.	Frequency of Analysis	Sample Type
Cadmium, Total Recoverable calculated limit) ARM Code 01113 Q	Sample Measurement Permit							Report ³	ug/L		Annually	Calculated
Ion Site No EFF-2 admium, Total Recoverable	Requirement Sample							(Max.)				
admium, Total Recoverable effluent minus calculated limit) ARM Code 01113 R	Measurement Permit		- No. 1					0.0	ug/L		Annually	Calculated
Ion Site No EFF-2	Requirement							(Max.)				
on, Total Recoverable ntake)	Sample Measurement						Report	Report	mg/L		Annually	24-hr TPC
ARM Code 00980 Q Ion. Site No. INT-1	Permit Requirement						(Mo Avg.)	(Day Max.)	-5-			
on, Total Recoverable effluent)	Sample Measurement						Panort	Report	mg/L		Annually	24-hr TPC
ARM Code 00980 1 Mon. Site No. EFF-2	Permit Requirement	Section 5					Report (Mo.Avg.)	(Day Max.)	AN E. I.	-	2 areauthri j	
on, Total Recoverable calculated limit)	Sample Measurement							- 4	mg/L		Annually	24-hr TPC
ARM Code 00980 1 Aon. Site No. EFF-2	Permit Requirement	And the second					Report ⁴ (Mo Avg.)	Report ⁴ (Day Max.)	mg/L		Aminany	24 111 110
on, Total Recoverable effluent minus calculated limit)	Sample Measurement								17		A Th	24-hr TPC
ARM Code 00980 1 Aon, Site No. EFF-2	Permit Requirement						0.0 (Mo.Avg.)	0.0 (Day Max.)	mg/L		Annually	24-m 11 C
ead, Total Recoverable Intake)	Sample Measurement							<u>.</u>	It		Athe	24-hr TPC
ARM Code 01114 S Aon, Site No. INT-1	Permit Requirement							Report (Max.)	ug/L		Annually	24-111 11 C
Lead, Total Recoverable effluent)	Sample Measurement				·						11.	24-hr TPC
PARM Code 01114 1 Mon Site No. EFF-2	Permit Requirement					e de la composition della comp		Report (Max.)	ug/L		Annually	24-m TrC
Lead, Total Recoverable calculated limit)	Sample Measurement										A 11.	Calculated
PARM Code 01114 Q Mon Site No. EFF-2	Permit Requirement							Report ³ (Max.)	ug/L		Annually	Calcinated
ead, Total Recoverable effluent minus calculated limit)	Sample Measurement											
PARM Code 01114 R Mon Site No EFF-2	Permit Requirement							0.0 (Max.)	ug/L		Annually	Calculated
Mercury, Total Recoverable Intake)	Sample Measurement											
PARM Code 71901 Q Mon. Site No. INT-1	Permit Requirement							Report (Max.)	ug/L		Annually	24-hr TPC

³ See Permit Conditions I.A.4 & I.A.5. If the concentration of the intake is greater than the limit calculated in Condition I.A.4, the intake concentration should be used as the effluent limit.

⁴ See Permit Condition I.A.5. If the concentration of the intake is greater than 1.0 mg/L, enter the intake value. If the concentration is less than 1.0 mg/L, enter 1.0 as the effluent limit.

DISCHARGE MONITORING REPORT - PART A (Continued)

FACILITY:

Scholz Electric Generating Plant

MONITORING GROUP

D-001

PERMIT NUMBER: FL0002283-004-IW1S

NUMBER:
MONITORING PERIOD From: ______ To: _____

Parameter		Quantity or Loading	Units	Quality o	r Concentration	Units	No. Ex.	Frequency of Analysis	Sample Type
Mercury, Total Recoverable	Sample Measurement					27		A 11	24-hr TPC
PARM Code 71901 1 Mon Site No. EFF-2	Permit Requirement		100		Report (Max.)	ug/L		Annually	24-in trc
Hardness, Total (as CaCO3)	Sample Measurement					mg/L		Annually	24-hr TPC
PARM Code 00900 1 Mon. Site No. EFF-2	Permit Requirement				Report (Max.)	шдуС		Annually	24-11 11 6
· ·									
			100 C 400 C					Section of the Association	
									200

When Completed mail t	his report to: Departmen	nt of Environm	ental Protectio	n, Wastewater Co	mpliance Evalua	tion Section, MS 3551,	2600 Blair Sto	ne Road, Tallahasse	e, FL 32399	-2400			
PERMITTEE NAME:	•	Gulf Power Company				PERMIT NUMBER: FL0002283-004-IW1S							
MAILING ADDRESS:		Pensacola, Florida 32520			LIMIT: . CLASS SIZE:			Final MA				Monthly Industrial	
FACILITY: LOCATION:	Scholz Electric Generating Plant 1460 Gulf Power Road Sneads, FL 32460						I-012 Ash Pond						
COUNTY: OFFICE:	Jackson Northwest District E	ranch (Panam	MONITORING PERIOD From: To: ama City)										
Paramet	Parameter		Quantity or Loading		Units	Quality or Concentration			Units	No. Ex.	Frequency of Analysis		
Flow	Sam Mea	ple surement									****	Calculated	
PARM Code 50050 P Mon. Site No. OUI-3	Pern Req	nit pirement		Report (Day Avg.)	MGD						Weekly	Carchiared	
Solids, Total Suspended	Sam Mea	ple surement						100.0	mg/L		Weekly	24-hr TPC	
PARM Code 00530 P Mon. Site No. OUI-3	Perr Req	nit uirement		are of the			30.0 (Mo.Avg.)	100.0 (Day Max.)	HIE/L		Weekiy	2711110	
Oil and Grease	Sam												

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	TELEPHONE NO	DATE (mm/dd/yyyy)
WANTED OF TANGET & STATE OF THE			i .

6.0

(Day.Min.)

COMMENT AND EXPLANATION OF ANY VIOLATIONS (Reference all attachments here):

Measurement

Requirement

Requirement

Permit

Sample Measurement

Permit

PARM Code 00556 P

PARM Code 00400 P

Mon. Site No. OUI-3

Mon. Site No. OUI-3

20.0

(Day.Max.)

9.0

(Day.Max.)

15.0

(Mo.Avg.)

mg/L

s.u.

Bi-weekly, every

2 weeks

Weekly

Grab

Grab

PERMITTEE NAME:	Gulf Power Co				PERN	AIT NUMBER	t:	FL00022	33-004-IW1S						
MAILING ADDRESS:	AILING ADDRESS: One Energy Place Pensacola, Florida 32520					LIMIT: CLASS SIZE:			Final MA			REPORT FREQUENCY: Annually PROGRAM: Industrial			
FACILITY: LOCATION:				MONITORING GROUP NUMBER: MONITORING GROUP DESCRIPTION: RE-SUBMITTED DMR: NO DISCHARGE FROM SITE:			I-012 Ash Pond								
COUNTY: OFFICE:					MONITORING PERIOD From:):					
Parameter			Quantity	or Loading	5	Units	Quality	or Concentra	ation	Units	No. Ex.	Frequency o Analysis	f Sample Typ		
Nickel, Total Recoverable		Sample Measurement											Grab		
PARM Code 01074 P Mon. Site No. OUI-3		Permit Requirement							Report (Inst.Max.)	ug/L		Annually	Grae		
			THE ANGESTER STATE OF THE STATE OF										The same of the same		
	and the second s														
				·											
			And the second s						Service Control						
The State of the S			3.23												
					1.77		AND AND DESCRIPTION OF	and the second				447			
I certify under penalty of l the information submitted	aw that this docu Based on my in	ment and all atta quiry of the pers	achments were prep	ared under manage th	my direc	tion or supervi	sion in accordance with ns directly responsible t	a system des for gathering t	igned to assure that on the information, the infolium in the infolium and im	qualified per nformation s prisonment	sonnel productions of the sound	roperly gather a d is, to the best ing violations.	nd evaluate of my		
knowledge and belief, true, accurate, and complete. I am aware that there are significant NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT				SIGNA	penalties for submitting false information, including the possibility of fine and implementation of principal executive officer or authorized agent					ELEPHO	NE NO DA	TE (mm/dd/yyyy)			
NAME/TITLE OF FRINCE	·														
COMMENT AND EVE	ANATION OF A	NIV VIOLATIO	NIC (Deference all	ettachment	s here)							L			

DEP Form 62-620.910(10), Effective Nov. 29, 1994

When Completed mail this report to: Department of Environmental Protection, Wastewater Compliance Evaluation Section, MS 3551, 2600 Blair Stone Road, Tallahassee, FL 32399-2400

PERMITTEE NAME: Gulf Power Company MAILING ADDRESS: One Energy Place					MIT NUMBE	R:		0002283-004-IW1S	EPORT FREQUENCY: Monthly			N. Grandlala			
	Pensacola, Flo	orida 32520		LIM	IT: .SS SIZE:					REPORT FREQUENCY: Monthly PROGRAM: Industrial					
FACILITY: LOCATION:						MONITORING GROUP NUMBER: MONITORING GROUP DESCRIPTION: RE-SUBMITTED DMR: NO DISCHARGE FROM SITE:				I-013 Domestic Wastewater Treatment Plant Effluent					
COUNTY: OFFICE:					NITORING PI			10							
Parameter	Γ		Quantity	or Loading	Units	Qu	ality or Co	ncentration	U	nits	No. Ex.	Frequency Analysis			
Flow		Sample Measurement										3371-1	Meter		
PARM Code 50050 P Mon. Site No OUI-4	Section 16	Permit Requirement	Report (Mo.Avg.)	Report (Day Max.)	MGD							Weekly	Meter		
				and the second second											
I certify under penalty of I the information submitted															
knowledge and belief, true, accurate, and complete. I am aware that there are significant NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT					t penalties for submitting false information, including the possibility of fine and imprison SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT						TELEPHONE NO		ATE (mm/dd/yyyy)		
COMMENT AND EYE	ANIATION OF A	NV VIOI ATION	NS (Reference all :	attachments here):											

DEP Form 62-620.910(10), Effective Nov. 29, 1994

When Completed mail th	is report to: Depar	tment of Enviror	nmental Protection	, Wastewater Com	pliance Evaluati	on Section, MS 3551,	, 2600 Blair Sto	one Road, Tallahasse	e, FL 32399	-2400		
PERMITTEE NAME:	Gulf Power Com			PERI	MIT NUMBER:		FL0002283-004-IW1S					
MAILING ADDRESS: One Energy Place Pensacola, Florida 32520				LIMI CLA	T: SS SIZE:		Final MA			r frequ AM:		Quarterly Industrial
FACILITY: LOCATION:		MONITORING GROUP NUMBER: I-013 MONITORING GROUP DESCRIPTION: Domestic Wastewater Treatment RE-SUBMITTED DMR: NO DISCHARGE FROM SITE:							nt Plant Effluent			
COUNTY: Jackson MONITORING PERIOD From: To:												
OFFICE:	Northwest Distr	ict Branch (Pana	ma City)									
Parameter			Quantity or Loading		Units	Quality or Concentration			Units	No. Ex.	Frequency of Analysis	of Sample Type
Biochemical Oxygen Dem	1	Sample Measurement						60.0			Ouarterly	Grab
PARM Code 00310 P Mon. Site No. OUI-4		Permit Requirement					30.0 (Mo.Avg.)	60 0 (Day Max.)	mg/L		Quarterry	- Crae
Solids, Total Suspended	i	Sample Measurement					20.0	60.0	mg/L		Quarterly	Grab
PARM Code 00530 P Mon. Site No. OUI-4		Permit Requirement			10.00		30.0 (Mo.Avg.)	60.0 (Day Max.)	mgru		Quarterry	- Jan
Coliform, Fecal	1	Sample Measurement					200		#/100mL		Quarterly	Grab
PARM Code 74055 Y Mon Site No OUI-4		Permit Requirement					200 (An Avg.)		#/100mil		Quarterly	(J, 10)

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	TELEPHONE NO	DATE (mm/dd/yyyy)
WAVE TILE OF FRICAL ENGINEERS TO STATE OF THE STATE OF TH			
	·		
		<u></u>	

COMMENT AND EXPLANATION OF ANY VIOLATIONS (Reference all attachments here):

Sample Measurement

Permit

Requirement

Coliform, Fecal

PARM Code 74055 P

Mon. Site No. OUI-4

800

(Max.)

200

(Mo.Geo.Mn.)

#/100mL

Grab

Quarterly

			GIV	JUNDYA		TILL ORGITY	G IGH OICE				
Facility Name: Permit Number: County: Office:	Scholz Electric Ge FL0002283-004-IV Jackson Northwest District	VIS	na City)			Wel Des	l Type: cription:	MWB-2051 Background MW-205S □	Report Frequency: Program:	Annually Industrial	
Monitoring Period		From:	***************************************	To:		Date	e Sample Obtained:				
-						Tim	e Sample Obtained:	appenditue reconstruction of the Section 1			
Was the well purged b	pefore sampling?	Ye	s No								
Para	meter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysis	Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative	to NGVD	82545		Report	ft	In Situ	Annually				
pН		00400		Report	s.u.	Grab	Annually				
Specific Conductance		00095		Report	umhos/cm	Grab	Annually				
Aluminum, Total Rec		01104		Report	mg/L	Grab	Annually				
Arsenic, Total Recove		00978		Report	mg/L	Grab	Annually				
Cadmium, Total Reco		01113		Report	mg/L	Grab	Annually				
Chloride (as Cl)		00940		Report	mg/L	Grab	Annually				
Chromium, Total Rec	coverable	01118		Report	mg/L	Grab	Annually				
Iron, Total Recoverat	ole	00980		Report	mg/L	Grab	Annually				ļ
Lead, Total Recovera	ible	01114		Report	mg/L	Grab	Annually				
Magnesium, Total	Recoverable	00921		Report	mg/L	Grab	Annually				
Mercury, Total Recov	verable	71901		Report	mg/L	Grab	Annually				
Selenium, Total Reco		00981		Report	mg/L	Grab	Annually				
Sulfate, Total		00945		Report	mg/L	Grab	Annually				
Solids, Total Dissolv	ed (TDS)	70295		Report	mg/L	Grab	Annually		<u> </u>		<u></u>
I certify under penalty information submitted belief, true, accurate,	y of law that this docu d. Based on my inqui and complete. I am a	ry of the person ware that there	n or persons who are significant p	enalties for submi	m, or those pe tting false inf	formation, includi		designed to assure that the information, the information and imprisonment for			aluate the owledge and
NAME/TITLE OF PR	INCIPAL EXECUTIVE	OFFICER OR A	UTHORIZED AGI	ENT S	IGNATURE O	F PRINCIPAL EX	ECUTIVE OFFICER OR	TO LITORIED AGENT			

Facility Name: Permit Number: County: Office:	Scholz Electric Ger FL0002283-004-IV Jackson Northwest District	VIS	na City)			We De	Il Type: scription:	MWB-2051 Background MW-205S	Report Frequency: Program:	Every 5 Yea Industrial	rs
Monitoring Period		From:		To:		Da	te Sample Obtained:				
						Tir	ne Sample Obtained:				
Was the well purged be	efore sampling?	Ye	s No							T	
Paran	neter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Alpha, Gross Particle	Activity	80045		Report	pCi/L	Grab	Once Every 5 Years				-
Radium 226 + Radium		11503		Report	pCi/L	Grab	Once Every 5 Years	7			
			·					_			
I certify under penalty information submitted belief, true, accurate,	y of law that this doct 1. Based on my inquand complete. I am	ument and all a iry of the perso aware that there	ttachments were n or persons who are significant p	enalties for subm	itting false in	formation, include	ling the possibility of fir	designed to assure that the information, the info ae and imprisonment for	knowing violations.		
	INCIPAL EXECUTIVE				SIGNATURE	OF PRINCIPAL E	XECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPHON	IE NO DATE (m	nm/dd/yyyy)
			,								
COMMENTS AND I	EXPLANATION (Re	eference all atta	chments here):								
7 When Gross Alpha	Particle Activity is d	 letected above 5	5.0 pCi/L, then co	ombined Radium 2	226 and 228	shall be tested an	d reported.				

DEP Form 62-620.910(10), Effective Nov. 29, 1994

	••	GRO	JUNDWAI	LEK MO	INITORIN	G REPORT - 1	PARID			
Permit Number: FL000228. County: Jackson	ctric Generating Plant 3-004-IWIS District Branch (Panam	a City)			Wel Des	nitoring Well ID: 1 Type: cription: submitted DMR:	MWC-2 Compliance WSW-2	Report Frequency: Program:	Annually Industrial	
Monitoring Period	From:		To:		Dat	e Sample Obtained:	NAME OF THE PROPERTY OF THE PR			
					Tim	e Sample Obtained:	· ·			
Was the well purged before sampling	ye?Ye	s No								
Parameter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative to NGVD	82545		Report	ft	In Situ	Annually				
рН	00400		Report	· s.u.	Grab	Annually				
Specific Conductance	00095		Report	umhos/cm	Grab	Annually				
Aluminum, Total Recoverable	01104		Report	mg/L	Grab	Annually				ļ
Arsenic, Total Recoverable	00978		Report	mg/L	Grab	Annually				ļ
Cadmium, Total Recoverable	01113		0.005	mg/L	Grab	Annually				
Chloride (as Cl)	00940		Report	mg/L	Grab	Annually				
Chromium, Total Recoverable	01118		0.100	mg/L	Grab	Annually				
Iron, Total Recoverable	00980		Report	mg/L	Grab	Annually				ļ
Lead, Total Recoverable	01114		0.015	mg/L	Grab	Annually				
Magnesium, Total Recoverable	00921		Report	mg/L	Grab	Annually				-
Mercury, Total Recoverable	71901		0.002	mg/L	Grab	Annually				
Selenium, Total Recoverable	00981		0.050	mg/L	Grab	Annually				<u> </u>
Sulfate, Total	00945		Report	mg/L	Grab	Annually	-			1
Solids, Total Dissolved (TDS)	70295		Report	mg/L	Grab	Annually	1			<u> </u>
I certify under penalty of law that t information submitted. Based on r belief, true, accurate, and complete	are impurious of the percent	or nercone who	manage the syster enalties for submi	m, or those pe tting false inf	ersons directly res formation, includi	ponsible for gathering ng the possibility of fin	e and imprisonment for	knowing violations.		
NAME/TITLE OF PRINCIPAL EXE	CUTIVE OFFICER OR A	JTHORIZED AGE	ENT S	IGNATURE O	F PRINCIPAL EX	ECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPHONI	E NO DATE (m	ım/dd/yyyy)

Facility Name: Permit Number: County: Office:	Scholz Electric Ge FL0002283-004-1 Jackson Northwest District	W1S t Branch (Panam	• •	T.		Wel Des Re-s	l Type: cription: submitted DMR:	MWC-2 Compliance WSW-2	Report Frequency Program:	: Every 5 Yea Industrial	ars
Monitoring Period	1	From:		10:			Sample Obtained:				
						1 im	e Sample Obtained:				
Was the well purged be	fore sampling?	Ye	s No			•					
Param	eter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysis	Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Alpha, Gross Particle A	ctivity	80045		15.0	pCi/L	Grab	Once Every 5 Years				
Radium 226 + Radium	228, Total	11503		5.0	pCi/L	Grab	Once Every 5 Years ⁸				
				,				·			
	Ŷ.					,					
				2							
		,	-								
	:										
	÷										
information submitted	Paced on my inqui	iru of the nerson	or persons who i	manage the syster	n or those ne	ersons directly resi	consible for gathering the	designed to assure that que information, the information and imprisonment for k	mation submitted is, t	perly gather and eva o the best of my kno	aluate the owledge and
NAME/TITLE OF PRIN	CIPAL EXECUTIVE	OFFICER OR A	JTHORIZED AGE	NT S	GNATURE O	F PRINCIPAL EXI	CUTIVE OFFICER OR A	UTHORIZED AGENT	TELEPHON	E NO DATE (m	m/dd/yyyy)
COMMENTS AND EX				nhined Radium 22	26 and 228 sh	nall be tested and r	eported.				

ISSUANCE/REISSUANCE DATE:

DEP Form 62-620.910(10), Effective Nov. 29, 1994

Facility Name: Permit Number: County: Office:	Scholz Electric Ge FL0002283-004-1 Jackson Northwest District	WIS	na City)			Wel Des	Type: cription:	MWC-203 Compliance MW-203MD □	Report Frequency: Program:	Annually Industrial	
Monitoring Period	1 to 1 to 2 to 2 to 2 to 2 to 2 to 2 to	From:		To:		Date	e Sample Obtained:				
						Tim	e Sample Obtained:	distribution to the first property and the second			
Was the well purged be	fore sampling?	Ye	s No						•		
Param	eter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysis	Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative to	NGVD	82545		Report	ft	In Situ	Annually				
рH		00400		Report	s.u.	Grab	Annually				
Specific Conductance		00095		Report	umhos/cm	Grab	Annually				
Aluminum, Total Reco	verable	01104		Report	mg/L	Grab	Annually				
Arsenic, Total Recover		00978		Report	mg/L	Grab	Annually				
Cadmium, Total Recov		01113		0.005	mg/L	Grab	Annually				
Chloride (as Cl)		00940		Report	mg/L	Grab	Annually				
Chromium Total Reco	verable	01118		0.100	mg/L	Grab	Annually				

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Grab

Grab

Grab

Grab

Grab

Grab

Grab

mg/L

mg/L

mg/L

mg/L

mg/L

mg/L

mg/L

Report

0.015

Report

0.002

0.050

Report

Report

Annually

Annually

Annually

Annually

Annually

Annually

Annually

NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	TELEPHONE NO	DATE (mm/dd/yyyy)
MANUEL TITLE OF TRANSPORTED BY ADDRESS OF THE PARTY OF TRANSPORTED BY ADDRESS OF THE PARTY OF TH			

COMMENTS AND EXPLANATION (Reference all attachments here):

Iron, Total Recoverable

Lead, Total Recoverable

Magnesium, Total Recoverable

Mercury, Total Recoverable

Selenium, Total Recoverable

Solids, Total Dissolved (TDS)

Sulfate, Total

00980

01114

00921

71901

00981

00945

70295

Facility Name: Permit Number: County: Office:	Scholz Electric G FL0002283-004- Jackson Northwest Distric	IW1S	na City)			Wel Des Re-	nitoring Well ID: 1 Type: cription: submitted DMR:	MWC-203 Compliance MW-203MD	Report Frequency: Program:	Every 5 Year Industrial	urs
Monitoring Period		From:		To:		Date	e Sample Obtained:	-			
						Tim	e Sample Obtained:	Acquire the second seco		•	
Was the well purged be	fore sampling?	Ye	s No				_				
Param	neter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Alpha, Gross Particle A	Activity	80045		15.0	pCi/L	Grab	Once Every 5 Years				
Radium 226 + Radium		11503		5.0	pCi/L	Grab	Once Every 5 Years	0			
	: : : ,				-						
											-
I certify under penalty information submitted belief true accurate.	of law that this do Based on my inq	cument and all a uiry of the perso	ttachments were persons who are significant p	orepared under m manage the syste enalties for subm	y direction of m, or those pitting false in	r supervision in acceptance of the supervision in acceptance of the supervision in acceptance of the supervision i	cordance with a system sponsible for gathering ng the possibility of fir	designed to assure that the information, the info are and imprisonment for	qualified personnel pro ormation submitted is, knowing violations.	operly gather and eve to the best of my kno	raluate the owledge and
NAME/TITLE OF PRI					SIGNATURE	OF PRINCIPAL EX	ECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPHON	E NO DATE (m	nm/dd/yyyy)
COMMENTS AND E	EXPLANATION (F	Reference all atta	chments here):								
9 When Gross Alpha	Particle Activity is	detected above 5	i.0 pCi/L, then co	mbined Radium 2	226 and 228	shall be tested and	reported.				

DEP Form 62-620.910(10), Effective Nov. 29, 1994

			GRO	JUNDWAJ	I EK MU	MIIOKIN	G REPORT - 1	ARID			
Facility Name: Permit Number: County: Office:	Scholz Electric Ge FL0002283-004-IV Jackson Northwest District	WIS	na City)			We Des	nitoring Well ID: Il Type: cription: submitted DMR:	MWC-2031 Compliance MW-203S	Report Frequency Program:	: Annually Industrial	
Monitoring Period		From:	4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-	To: _		Dat	e Sample Obtained:	Water Control of the Control of C			
						Tin	ne Sample Obtained:	***************************************			
Was the well purged	pefore sampling?	Ye	es No								
Para	meter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative	to NGVD	82545		Report	ft	In Situ	Annually				
рН		00400		Report	s.u.	Grab	Annually				
Specific Conductanc		00095		Report	umhos/cm	Grab	Annually				-
Aluminum, Total Re		01104		Report	mg/L	Grab	Annually				
Arsenic, Total Recov	erable	00978		Report	mg/L	Grab	Annually				
Cadmium, Total Rec	overable	01113		0.005	mg/L	Grab	Annually				<u> </u>
Chloride (as Cl)	`	00940		Report	mg/L	Grab	Annually				-
Chromium, Total Re	coverable	01118		0.100	mg/L	Grab	Annually				
Iron, Total Recovera	ble	00980		Report	mg/L	Grab	Annually				
Lead, Total Recover	able	01114		0.015	mg/L	Grab	Annually				
Magnesium, Total R	ecoverable	00921		Report	mg/L	Grab	Annually				
Mercury, Total Reco		71901		0.002	mg/L	Grab	Annually				
Selenium, Total Rec	overable	00981		0.050	mg/L	Grab	Annually				
Sulfate, Total		00945		Report	mg/L	Grab	Annually				
Solids, Total Dissolv		70295		Report	mg/L	Grab	Annually		<u> </u>		<u> </u>
information submitted belief, true, accurate	 d. Based on my inqui and complete. I am a 	ry of the person ware that there	n or persons who are significant po	enalties for submi	m, or those pe itting false inf	formation, includi	ng the possibility of fin	designed to assure that the information, the information and imprisonment for			valuate the nowledge and
NAME/TITLE OF P	INCIPAL EXECUTIVE	OFFICER OR A	UTHORIZED AGE	INT S	SIGNATURE C	F PRINCIPAL EX	ECUTIVE OFFICER OR	AUTHURIZED AGENT	TELEPHON	Ditte (iii	

Facility Name: Permit Number: County; Office:	Scholz Electric Ge FL0002283-004-1 Jackson Northwest District	W1S	na City)			Wel Des Re-s	nitoring Well ID: I Type: cription: submitted DMR:	MWC-2031 Compliance MW-203S	Report Frequency: Program:	Every 5 Yea Industrial	ars
Monitoring Period		From:		To:	<u> </u>		e Sample Obtained:				
						Tim	e Sample Obtained:	-			
Was the well purged b	pefore sampling?	Ye	s No								
Para	meter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Alpha, Gross Particle	Activity	80045		15.0	pCi/L	Grab	Once Every 5 Years				
Radium 226 + Radiu		11503		5.0	pCi/L	Grab	Once Every 5 Years	.0			
					<u> </u>						
									-		
								,			
					· · · · · · · · · · · · · · · · · · ·						
											<u></u>
				manage the system enalties for submi	m, or those p tting false in	formation, includi	ng the possibility of fir	the information, the info ne and imprisonment for	knowing violations.	,	
	RINCIPAL EXECUTIVE				IGNATURE (OF PRINCIPAL EX	ECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPHON	E NO DATE (m	ım/dd/yyyy)
COMMENTS AND	EXPLANATION (Re	eference all atta	chments here):								
		articipant.									
10 When Gross Alph	a Particle Activity is	detected above :	5.0 pCi/L, then co	ombined Radium 2	226 and 228	shall be tested and	геропеа,				

DEP Form 62-620.910(10), Effective Nov. 29, 1994

Permit Number: County:	Scholz Electric Ger FL0002283-004-IW Jackson Jorthwest District	/1S	na City)			Wel Des	l Type: cription:	MWC-204 Compliance MW-204MD	Report Frequency: Program:	Annually Industrial	
Monitoring Period		From:		To:		Date	e Sample Obtained:	-4			
						Tim	e Sample Obtained:	and the same of th			
Was the well purged before	re sampling?	Ye	s No								
Parame	ter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysis	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative to	NGVD	82545		Report	ft	In Situ	Annually				
pН		00400		Report	s.u.	Grab	Annually				
Specific Conductance		00095		Report	umhos/cm	Grab	Annually				
Aluminum, Total Recove	erable	01104		Report	mg/L	Grab	Annually				
Arsenic, Total Recovera	ble	00978		Report	mg/L	Grab	Annually				
Cadmium, Total Recove	j.	01113	-	0.005	mg/L	Grab	Annually				
Chloride (as Cl)		00940		Report	mg/L	Grab	Annually				
Chromium, Total Recov	erable	01118		0.100	mg/L	Grab	Annually				
Iron, Total Recoverable		00980		Report	mg/L	Grab	Annually				
Lead, Total Recoverable		01114		0.015	mg/L	Grab	Annually				
Magnesium, Total Reco	verable	00921		Report	mg/L	Grab	Annually				
Mercury, Total Recover	able	71901		0.002	mg/L	Grab	Annually				
Selenium, Total Recove	Control	00981		0.050	mg/L	Grab	Annually				
Sulfate, Total		00945		Report	mg/L	Grab	Annually				
Solids, Total Dissolved	(TDS)	70295		Report	mg/L	Grab	Annually			<u> </u>	<u> </u>
I certify under penalty of information submitted, belief, true, accurate, and NAME/TITLE OF PRING	Based on my inquir d complete. I am a	y of the persor ware that there	or persons who are significant pe	manage the system enalties for submi	m, or those pe tting false inf	ormation, includi	nonsine for gameing i	e and imprisonment for l	illiation sacrimeted to,		aluate the owledge and
COMMENTS AND EX											
COMMENTO THE DA											

DEP Form 62-620.910(10), Effective Nov. 29, 1994

Permit Number: County:	Scholz Electric Ge FL0002283-004-IV Jackson Northwest District	W1S Branch (Panam				We Des	nitoring Well ID: Il Type: cription: submitted DMR:	MWC-204 Compliance MW-204MD	Report Frequency: Program:	Every 5 Yes Industrial	ars
Monitoring Period	HANNEY YOU	From:		To: _		Dat	e Sample Obtained:	when the same and an arrangements			
						Tim	ne Sample Obtained:				
Was the well purged bef	ore sampling?	Ye	s No								-
Paramo	eter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Alpha, Gross Particle A	ctivity	80045		15.0	pCi/L	Grab	Once Every 5 Years				
Radium 226 + Radium 2		11503		5.0	pCi/L	Grab	Once Every 5 Years ¹	1			
	To the second se										
					<u> </u>						<u> </u>
-		<u> </u>			-						
					<u>.</u>			·			
·											
										L	<u> </u>
	m i i	we of the norgan	or narcone who	manage the cycte	m or those n	ersons directivites	nonsinie ioi gamenne:	designed to assure that of the information, the information and imprisonment for l	illiation sublitition is, t	perly gather and ev o the best of my kn	aluate the owledge and
NAME/TITLE OF PRIN	4						ECUTIVE OFFICER OR		TELEPHON	E NO DATE (m	ım/dd/yyyy)
		ð									
COMMENTS AND EX	in with the field of the field										
11 When Gross Alpha I	Particle Activity is o	letected above 5	0.0 pCi/L, then co	ombined Radium	226 and 228	shall be tested and	I reported.				

ISSUANCE/REISSUANCE DATE:

DEP Form 62-620.910(10), Effective Nov. 29, 1994

Monitoring Well ID:

MWC-210

Facility Name: Permit Number: County: Office:	Scholz Electric Ge FL0002283-004-IV Jackson Northwest District	WIS	na City)			Wel Des		MWC-210 Compliance MW-210MD	Report Frequency: Program:	Annually Industrial	
Monitoring Period		From:		To: _		Date	e Sample Obtained:				
						Tim	e Sample Obtained:	Appendix of the systems			
Was the well purged be	fore sampling?	Ye	s No								
Param	ieter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative to	NGVD	82545		Report	ft	In Situ	Annually				
pH		00400		Report	s.u.	Grab	Annually				
Specific Conductance		00095		Report	umhos/cm	Grab	Annually				
Aluminum, Total Reco	verable	01104		Report	mg/L	Grab	Annually				
Arsenic, Total Recover		00978		Report	mg/L	Grab	Annually				
Cadmium, Total Recov	:	01113		0.005	mg/L	Grab	Annually				
Chloride (as Cl)	·	00940		Report	mg/L	Grab	Annually				
Chromium, Total Reco	overable	01118		0.100	mg/L	Grab	Annually				
Iron, Total Recoverabl		00980		Report	mg/L	Grab	Annually				ļ
Lead, Total Recoverab	1	01114		0.015	mg/L	Grab	Annually				
Magnesium, Total Rec		00921		Report	mg/L	Grab	Annually				
Mercury, Total Recove		71901		0.002	mg/L	Grab	Annually				
Selenium, Total Recov		00981		0.050	mg/L	Grab	Annually				ļ
Sulfate, Total		00945		Report	mg/L	Grab	Annually				
Solids Total Dissolve	d (TDS)	70295		Report	mg/L	Grab	Annually				
I certify under penalty	of law that this docu	ument and all a iry of the person aware that there	ttachments were part or persons who are significant p	orepared under m manage the syste enalties for subm	ny direction or em, or those po nitting false inf	supervision in ac ersons directly res formation, includi	cordance with a system sponsible for gathering ng the possibility of fin	designed to assure that the information, the info e and imprisonment for	qualified personnel pro rmation submitted is, knowing violations.		
NAME/TITLE OF PRI					SIGNATURE C	F PRINCIPAL EX	ECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPHON	IE NO DATE (n	nm/dd/yyyy)
								,			

DEP Form 62-620.910(10), Effective Nov. 29, 1994

Facility Name: Scholz Electric Generating Plant Permit Number: FL0002283-004-IW1S County: Jackson Office: Northwest District Branch (Panama City)						We Des	Il Type:	MWC-210 Compliance MW-210MD	Report Frequency: Program:	Every 5 Yea Industrial	rs
Monitoring Period		From:		To:		Dat	e Sample Obtained:				
						Tin	ne Sample Obtained:				
Was the well purged b	pefore sampling?	Ye	s No								
Para	meter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Alpha, Gross Particle	Activity	80045		15.0	pCi/L	Grab	Once Every 5 Years				
Radium 226 + Radiur		11503		5.0	pCi/L	Grab	Once Every 5 Years ¹	2			
								·			
					†						
										<u> </u>	<u> </u>
I certify under penaltinformation submitte	ty of law that this do	cument and all a uiry of the perso	ttachments were properties of the state of t	orepared under my manage the syste enalties for submi	y direction or m, or those p itting false in	r supervision in ac persons directly re aformation, includ	ecordance with a system sponsible for gathering ing the possibility of fir	the information, the information, the information the information the information that imprisonment for	qualified personnel pro rmation submitted is, t knowing violations.	operly gather and ev to the best of my kn	raluate the owledge and
	RINCIPAL EXECUTIV				SIGNATURE	OF PRINCIPAL EX	CECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPHON	E NO DATE (n	nm/dd/yyyy)
TARREST TIES OF TA							·				
COMMENTS AND	EXPLANATION (F	Reference all atta	chments here):			·					
							1				
12 When Gross Alph	na Particle Activity is	detected above	5.0 pCi/L, then c	ombined Radium	226 and 228	shall be tested an	а геропеа.	•			

DEP Form 62-620.910(10), Effective Nov. 29, 1994

Facility Name: Permit Number: County: Office:	mit Number: FL0002283-004-IW1S unty: Jackson ice: Northwest District Branch (Panama City)					Wel Des	l Type:	MWC-212 Compliance MW-212MD	Report Frequency: Program:	Annually Industrial	
Monitoring Period		From:		To:			e Sample Obtained: e Sample Obtained:				
Was the well purged be	efore sampling?	Ye	s No			1111	e dampie Obtained.				
Paran	neter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysis	Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative t	to NGVD	82545	-	Report	ft	In Situ	Annually				
рН		00400		Report	s.u.	Grab	Annually				
Specific Conductance	-	00095		Report	umhos/cm	Grab	Annually				
Aluminum, Total Reco		01104		Report	mg/L	Grab	Annually		<u> </u>		
Arsenic, Total Recove	•	00978		Report	mg/L	Grab	Annually				
Cadmium, Total Reco		01113		0.005	mg/L	Grab	Annually				

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Grab

Grab

Grab

Grab

Grab

Grab

Grab

Grab

Grab

mg/L

mg/L

mg/L

mg/L

mg/L

mg/L

mg/L

mg/L

mg/L

Report

0.100

Report

0.015

Report

0.002

0.050

Report

Report

Annually

Annually

Annually

Annually

Annually

Annually

Annually

Annually

Annually

TOURS TIES OF TAXONIC STATES			
NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	TELEPHONE NO	DATE (mm/dd/yyyy)

COMMENTS AND EXPLANATION (Reference all attachments here):

Chloride (as Cl)

Sulfate, Total

Chromium, Total Recoverable

Magnesium, Total Recoverable

Mercury, Total Recoverable

Selenium, Total Recoverable

Solids, Total Dissolved (TDS)

Iron, Total Recoverable

Lead, Total Recoverable

00940

01118

00980

01114

00921

71901

00981

00945

70295

Facility Name: Scholz Electric Generating Plant Permit Number: FL0002283-004-IW1S County: Jackson Office: Northwest District Branch (Panama City)		na City)			We De	ell Type: scription:	MWC-212 Compliance MW-212MD	Report Frequency: Program:	Every 5 Yea Industrial	ars	
Monitoring Period		From:	***************************************	To:		Da	te Sample Obtained:				
						Ti	me Sample Obtained:				
Was the well purged l	before sampling?	Ye	s No					_			<u> </u>
Para	nmeter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Alpha, Gross Particle	Activity	80045		15.0	pCi/L	Grab	Once Every 5 Years		·		
Radium 226 + Radiu		11503		5.0	pCi/L	Grab	Once Every 5 Years ¹	3			
						1					
					-						
						·					
						·					
						-					
				-							
I certify under penal information submitt belief, true, accurate	ty of law that this doc ed. Based on my inque, and complete. I am	nument and all a niry of the perso aware that there	ttachments were n or persons who e are significant p	enalties for subm	itting false in	formation, inclu	ding the possibility of fir	n designed to assure that the information, the info ne and imprisonment for	qualified personnel pro rmation submitted is, t knowing violations.		valuate the nowledge and
NAME/TITLE OF P	RINCIPAL EXECUTIV	E OFFICER OR A	AUTHORIZED AG	ENT	SIGNATURE	OF PRINCIPAL E	XECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPHON	ENO DATE (II	minda yyyy)
	EXPLANATION (R										
13 When Grees Aln	ha Particle Activity is	detected above	5.0 pCi/L, then o	ombined Radium	226 and 228	shall be tested a	nd reported.				

DEP Form 62-620.910(10), Effective Nov. 29, 1994

Facility Name: Permit Number: County:	Scholz Electric Generating Plant FL0002283-004-IW1S Jackson		Monitoring Well ID: Well Type: Description:	MWI-204S Intermediate MWI-204S, Intermediate	Report Frequency: Program:	Annually Industrial
Office:	Northwest District Branch (Panama City)		Re-submitted DMR:			
Monitoring Period	From:	To:	Date Sample Obtained:			
			Time Sample Obtained:			
Was the well purged be	fore sampling?Yes No					

Parameter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysis	Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative to NGVD	82545		Report	ft	In Situ	Annually				
рН	00400		Report	s.u.	Grab	Annually				
Specific Conductance	00095		Report	umhos/cm	Grab	Annually				
Aluminum, Total Recoverable	01104		Report	mg/L	Grab	Annually				
Arsenic, Total Recoverable	00978		Report	mg/L	Grab	Annually				
Cadmium, Total Recoverable	01113		Report	mg/L	Grab	Annually				
Chloride (as Cl)	00940		Report	mg/L	Grab	Annually				
Chromium, Total Recoverable	01118		Report	mg/L	Grab	Annually				
Iron, Total Recoverable	00980		Report	mg/L	Grab	Annually				
Lead, Total Recoverable	01114		Report	mg/L	Grab	Annually				-
Magnesium, Total Recoverable	00921		Report	mg/L	Grab	Annually				<u> </u>
Mercury, Total Recoverable	71901		Report	mg/L	Grab	Annually				
Selenium, Total Recoverable	00981		Report	mg/L	Grab	Annually				-
Sulfate, Total	00945		Report	mg/L	Grab	Annually				
Solids, Total Dissolved (TDS)	70295		Report	mg/L	Grab	Annually		<u> </u>		<u></u>

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

NAME/ITILE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT			
NAME/TITLE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	TELEPHONE NO	DATE (min/du/yyyy)
benet, ade, avvalue, see a see a		mor povionin nio	DATE (mm/dd/yyyy)

Facility Name: Permit Number: County:	Scholz Electric Go FL0002283-004-I Jackson Northwest Distric	WIS	oo City)			We Des	nitoring Well ID: Il Type: scription: submitted DMR:	MWI-204S Intermediate MWI-204S, Intermediate	Report Frequer Program:		ery 5 Year lustrial	s
Office:	Northwest Distric			To			e Sample Obtained:					
Monitoring Period		From:		10			ne Sample Obtained:	- And Annual Control of the Control				
Was the well purged b	pefore sampling?	Ye	s No			1 10	To Sumpto Common				·	1
Para	meter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	d Samp Equipme		Samples Filtered (L/F/N)
Alpha, Gross Particle	Activity	80045		Report	pCi/L	Grab	Once Every 5 Years					
Radium 226 + Radiur		11503		Report	pCi/L	Grab	Once Every 5 Years ¹	4				
Teacher 220 Teacher												
										-		
					-							
					-							
					-							
					-							
				manage the syste enalties for subm	m, or those p itting false in	formation, includ	ing the possibility of fin	designed to assure that q the information, the infor e and imprisonment for k	nowing violations	3.	-	
	RINCIPAL EXECUTIV				SIGNATURE (OF PRINCIPAL EX	ECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPH	IONE NO	DATE (mr	n/dd/yyyy)
						,						
COMMENTS AND	EXPLANATION (R	eference all attac	chments here):									
14 When Gross Alph	a Particle Activity is	detected above	5.0 pCi/L, then co	ombined Radium	226 and 228	shall be tested an	d reported.					

DEP Form 62-620.910(10), Effective Nov. 29, 1994

			GRU	JUND WA.	IEK MO	TATT OTCH	o itali oiti i				
Facility Name: Permit Number: County:	Scholz Electric Ge FL0002283-004-1 Jackson	enerating Plant W1S				Wel Des		MWI-210S Intermediate MWI- 210S,Intermediate	Report Frequency: Program:	Annually Industrial	
Office:	Northwest Distric	t Branch (Panam	na City)				submitted DMR:				
Monitoring Period		From:		To: _			e Sample Obtained:				
						Tim	e Sample Obtained:				
Was the well purged b	efore sampling?	Ye	s No								
Para	meter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative	to NGVD	82545		Report	ft	In Situ	Annually				
pH	1011012	00400		Report	s.u.	Grab	Annually				
Specific Conductance		00095		Report	umhos/cm	Grab	Annually				
Aluminum, Total Rec		01104		Report	mg/L	Grab	Annually				
Arsenic, Total Recov		00978		Report	mg/L	Grab	Annually				
Cadmium, Total Reco		01113		Report	mg/L	Grab	Annually				
Chloride (as Cl)		00940		Report	mg/L	Grab	Annually				
Chromium, Total Re	coverable	01118		Report	mg/L	Grab	Annually				
Iron, Total Recovera		00980		Report	mg/L	Grab	Annually				
Lead, Total Recovers		01114		Report	mg/L	Grab	Annually		<u> </u>		
Magnesium, Total		00921 .		Report	mg/L	Grab	Annually				
Mercury, Total Reco		71901		Report	mg/L	Grab	Annually				
Selenium, Total Rec		00981		Report	mg/L	Grab	Annually				
Sulfate, Total		00945		Report	mg/L	Grab	Annually			-	1
S 11 1 T 1 1 D 1 1 1 1	ed (TDS)	70295		Report	mg/L	Grab	Annually				(aluate the
I certify under penalt	ry of law that this do	cument and all a uiry of the perso	ttachments were n or persons who e are significant p	enalties for subn	nitting false in	formation, includ	ing the possibility of fi	the information, the information and imprisonment for	knowing violations.		
	RINCIPAL EXECUTIV				SIGNATURE (OF PRINCIPAL EX	ECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPHON	IE NO DATE (1	nm/dd/yyyy)

Facility Name: Permit Number: County: Office: Monitoring Period	Scholz Electric (FL0002283-004 Jackson Northwest Distr	-IW1S ict Branch (Panam				Well Type: Description: Re-submitted DMR:		MWI-210S Intermediate MWI- 210S,Intermediate	Report Frequency: Program:	Every 5 Yea Industrial	irs
Was the well purged	hefore sampling?	Ye	s No			1 1111	e Sample Obtained.	Amagining the Continue for the American			
	ameter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	is Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Alpha, Gross Particle	- Δctivity	80045		Report	pCi/L	Grab	Once Every 5 Years	3			
Radium 226 + Radiu		11503		Report	pCi/L	Grab	Once Every 5 Years	15			
				:							
							,				
·											
											1.
I certify under pena information submitt belief, true, accurate	Ity of law that this died. Based on my ine, and complete. I a	ocument and all a quiry of the perso m aware that there	ttachments were n or persons who e are significant p	enalties for subm	itting false in	formation, includ	ing the possibility of fi	n designed to assure that the information, the info ne and imprisonment for	knowing violations.		valuate the nowledge an
	PRINCIPAL EXECUT				SIGNATURE	OF PRINCIPAL EX	ECUTIVE OFFICER OR	AUTHORIZED AGENT	TELEPHON	ENO DATE (II	minuwyyyy)
COMMENTS AND											

A I minorio i somi ing ito decentral modernite. The second second

Facility Name: Permit Number: County:	Scholz Electric Ger FL0002283-004-IV Jackson					Wel	nitoring Well ID: l Type: cription:	MWP-103 Piezometer MW-103; Monitoring Piezometer well.	Report Frequency: Program:	Annual Industrial	
Office:	Northwest District	Branch (Panan	na City)			Re-	submitted DMR:				
Monitoring Period		From:		To:		Dat	e Sample Obtained:	The second secon			
						Tim	e Sample Obtained:	April a processor and the order of the first time.			
Was the well purged be	fore sampling?	Ye	s No								
Paran	neter	PARM Code	Sample Measurement	Permit Requiremen	Units	Sample Type	Frequency of Analysi	s Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative t	o NGVD	82545		Report	ft	In Situ	Quarterly		·		
I certify under penalty	of law that this docur Based on my inquir and complete. I am av	y of the person ware that there	or persons who are significant pe	manage the systematics for subr	tem, or those pe nitting false inf	formation, including	nonsinie ioi gameinie i	designed to assure that q he information, the infor e and imprisonment for k AUTHORIZED AGENT	mucion buomineda io, o		lluate the wledge and

Facility Name: Permit Number: County:	Scholz Electric Ger FL0002283-004-IV Jackson	•				Wel	Type:	MWP-105 Piezometer MW-105; Monitoring Piezometer well.	Report Frequence Program:	y: Annual Industrial	
Office:	Northwest District	Branch (Panan	na City)			Re-	ubmitted DMR:				
Monitoring Period		From:		To:		Date	Sample Obtained:	Account to the south of the			
						Tim	e Sample Obtained:	- Light and the			
Was the well purged be	efore sampling?	Ye	s No				·				
Paran	neter	PARM Code	Sample Measurement	Permit Requiremen	Units	Sample Type	Frequency of Analysi	S Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative t	to NGVD	82545		Report	ft	In Situ	Quarterly				
I certify under penalty	of law that this docur		or norcone tubo t	manage the cycl	tem or those be	TSOUS OHECHA ICSI	onsidic for gamering c	designed to assure that que information, the information and imprisonment for k	ALLGEROLD DEFENDENCE IN THE	operly gather and e to the best of my k	valuate the nowledge and
NAME/TITLE OF PRIN					SIGNATURE O	F PRINCIPAL EXE	CUTIVE OFFICER OR A	AUTHORIZED AGENT	TELEPHO	NE NO DATE (mm/dd/yyyy)
171111111111111111111111111111111111111											

DEP Form 62-620.910(10), Effective Nov. 29, 1994

Facility Name: Permit Number: County:	Scholz Electric Generating Plant FL0002283-004-IW1S Jackson					Wel	l Type: cription:	MWP-110 Piezometer MW-110A; Monitoring Piezometer well.	Report Frequency: Program:	Annual Industrial	
Office:	Northwest District Branch (Panama City)					Re-	submitted DMR:				
Monitoring Period	From:			To:		Date	e Sample Obtained:	The second state of the se			
-						Tim	e Sample Obtained:				
Was the well purged b	efore sampling?	Ye	s No								r
Parai	neter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	S Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
Water Level Relative	to NGVD	82545		Report	ft	In Situ	Quarterly				
I certify under penalty information submitted belief, true, accurate, a	of law that this docur . Based on my inquir and complete. I am av	y of the person ware that there	or persons who are significant pe	manage the syste	itting false inf	formation, including		designed to assure that q he information, the infor and imprisonment for k			aluate the owledge and only only only only only only only only
NAME/TITLE OF PRI	NCIPAL EXECUTIVE	OFFICER OR A	JTHORIZED AGE	NT	SIGNATURE C	PRINCIPAL EXI	COTIVE OFFICER OR A	TOTTIONIZED AUDINI			

Facility Name: Permit Number: County: Office: Monitoring Period	Scholz Electric Generating Plant FL0002283-004-IW1S Jackson Northwest District Branch (Panama City) From:				Wel Desc Re-s Date	Type:	MWP-112 Piezometer MW-112; Monitoring Piezometer well.	Report Frequency: Program:	Annual Industrial		
Was the well purged be	fore sampling?	Ye	s No							T	
Paran	neter	PARM Code	Sample Measurement	Permit Requirement	Units	Sample Type	Frequency of Analysi	S Detection Limits	Analysis Method	Sampling Equipment Used	Samples Filtered (L/F/N)
							0 1 1			-	
Water Level Relative t	o NGVD	82545		Report	ft	In Situ	Quarterly				
L certify under penalty	of law that this docum Based on my inquiry and complete. I am av	vare that there	are significant pe	enalties for subr	nitting false inf	formation, including	ordance with a system consible for gathering in general the possibility of fin accuracy of the possibility of fin accuracy of the possibility of fin accuracy of the possibility of the	designed to assure that q the information, the infor e and imprisonment for k AUTHORIZED AGENT	ualified personnel pro mation submitted is, t mowing violations.		aluate the owledge and

INSTRUCTIONS FOR COMPLETING THE WASTEWATER DISCHARGE MONITORING REPORT

Read these instructions before completing the DMR. Hard copies and/or electronic copies of the required parts of the DMR were provided with the permit. All required information shall be completed in full and typed or printed in ink. A signed, original DMR shall be mailed to the address printed on the DMR by the 28th of the month following the monitoring period. The DMR shall not be submitted before the end of the monitoring period.

The DMR consists of three parts--A, B, and D--all of which may or may not be applicable to every facilities may have one or more Part A's for reporting effluent or reclaimed water data. All domestic wastewater facilities will have a Part B for reporting daily sample results. Part D is used for reporting ground water monitoring well data.

When results are not available, the following codes should be used on parts A and D of the DMR and an explanation provided where appropriate. Note: Codes used on Part B for raw data are different.

CODE	DESCRIPTION/INSTRUCTIONS
	1 1 i de la casa de la
ANC	Analysis not conducted.
DRY	Dry Well
FLD	Flood disaster.
IFS	Insufficient flow for sampling.
LS	Lost sample.
	Lost sample.
MNR	Monitoring not required this period.

CODE	DESCRIPTION/INSTRUCTIONS	
NOD OPS OTH SEF	No discharge from/to site. Operations were shutdown so no sample could be taken. Other. Please enter an explanation of why monitoring data were not available. Sampling equipment failure.	

When reporting analytical results that fall below a laboratory's reported method detection limits or practical quantification limits, the following instructions should be used:

- 2. Results less than the PQL and greater than or equal to the MDL shall be reported as the laboratory's MDL value. These values shall be deemed equal to the MDL when necessary to calculate an average for that parameter and
- 3. Results less than the MDL shall be reported by entering a less than sign ("<") followed by the laboratory's MDL value, e.g. < 0.001. A value of one-half the MDL or one-half the effluent limit, whichever is lower, shall be used for that sample when necessary to calculate an average for that parameter. Values less than the MDL are considered to demonstrate compliance with an effluent limitation.

PART A -DISCHARGE MONITORING REPORT (DMR)

Part A of the DMR is comprised of one or more sections, each having its own header information. Facility information is preprinted in the header as well as the monitoring group number, whether the limits and monitoring requirements are interim or final, and the required submittal frequency (e.g. monthly, annually, quarterly, etc.). Submit Part A based on the required reporting frequency in the header and the instructions shown in the permit. The following should be completed by the permittee or authorized representative:

Resubmitted DMR: Check this box if this DMR is being re-submitted because there was information missing from or information that needed correction on a previously submitted DMR. The information that is being revised No Discharge From Site: Check this box if no discharge occurs and, as a result, there are no data or codes to be entered for all of the parameters on the DMR for the entire monitoring group number; however, if the monitoring

group includes other monitoring locations (e.g., influent sampling), the "NOD" code should be used to individually denote those parameters for which there was no discharge.

Monitoring Period: Enter the month, day, and year for the first and last day of the monitoring period (i.e. the month, the quarter, the year, etc.) during which the data on this report were collected and analyzed.

Sample Measurement: Before filling in sample measurements in the table, check to see that the data collected correspond to the limit indicated on the DMR (i.e. interim or final) and that the data correspond to the monitoring group number in the header. Enter the data or calculated results for each parameter on this row in the non-shaded area above the limit. Be sure the result being entered corresponds to the appropriate statistical base code (e.g. annual average, monthly average, single sample maximum, etc.) and units.

No. Ex.: Enter the number of sample measurements during the monitoring period that exceeded the permit limit for each parameter in the non-shaded area. If none, enter zero.

Frequency of Analysis: The shaded areas in this column contain the minimum number of times the measurement is required to be made according to the permit. Enter the actual number of times the measurement was made in the

Sample Type: The shaded areas in this column contain the type of sample (e.g. grab, composite, continuous) required by the permit. Enter the actual sample type that was taken in the space above the shaded area.

Signature: This report must be signed in accordance with Rule 62-620.305, F.A.C. Type or print the name and title of the signing official. Include the telephone number where the official may be reached in the event there are

Comment and Explanation of Any Violations: Use this area to explain any exceedances, any upset or by-pass events, or other items which require explanation. If more space is needed, reference all attachments in this area.

PART B - DAILY SAMPLE RESULTS

Monitoring Period: Enter the month, day, and year for the first and last day of the monitoring period (i.e. the month, the quarter, the year, etc.) during which the data on this report were collected and analyzed. Daily Monitoring Results: Transfer all analytical data from your facility's laboratory or a contract laboratory's data sheets for all day(s) that samples were collected. Record the data in the units indicated. Table 1 in Chapter 62-160, F.A.C., contains a complete list of all the data qualifier codes that your laboratory may use when reporting analytical results. However, when transferring numerical results onto Part B of the DMR, only the following data qualifier codes should be used and an explanation provided where appropriate.

CODE	DESCRIPTION/INSTRUCTIONS
<	The compound was analyzed for but not detected.
A	Value reported is the mean (average) of two or more determinations.
1	Estimated value, value not accurate.
-	Sample held beyond the actual holding time.
	Laboratory analysis was from an unpreserved or improperly preserved sample.
1 T	Laboratory analysis was from an unpreserved of impropriate

To calculate the monthly average, add each reported value to get a total. For flow, divide this total by the number of days in the month. For all other parameters, divide the total by the number of observations.

Plant Staffing: List the name, certificate number, and class of all state certified operators operating the facility during the monitoring period. Use additional sheets as necessary.

PART D - GROUND WATER MONITORING REPORT

Monitoring Period: Enter the month, day, and year for the first and last day of the monitoring period (i.e. the month, the quarter, the year, etc.) during which the data on this report were collected and analyzed.

Date Sample Obtained: Enter the date the sample was taken. Also, check whether or not the well was purged before sampling.

Time Sample Obtained: Enter the time the sample was taken.

Sample Measurement: Record the results of the analysis. If the result was below the minimum detection limit, indicate that.

Detection Limits: Record the detection limits of the analytical methods used.

Analysis Method: Indicate the analytical method used. Řecord the method number from Chapter 62-160 or Chapter 62-601, F.A.C., or from other sources.

Sampling Equipment Used: Indicate the procedure used to collect the sample (e.g. airlift, bucket/bailer, centrifugal pump, etc.)

Samples Filtered: Indicate whether the sample obtained was filtered by laboratory (L), filtered in field (F), or unfiltered (N).

Signature: This report must be signed in accordance with Rule 62-620.305, F.A.C. Type or print the name and title of the signing official. Include the telephone number where the official may be reached in the event there are questions concerning this report. Enter the date when the report is signed.

Comments and Explanation: Use this space to make any comments on or explanations of results that are unexpected. If more space is needed, reference all attachments in this area.

SPECIAL INSTRUCTIONS FOR LIMITED WET WEATHER DISCHARGES

Flow (Limited Wet Weather Discharge): Enter the measured average flow rate during the period of discharge or divide gallons discharged by duration of discharge (converted into days). Record in million gallons per day

Flow (Upstream): Enter the average flow rate in the receiving stream upstream from the point of discharge for the period of discharge. The average flow rate can be calculated based on two measurements; one made at the start and one made at the end of the discharge period. Measurements are to be made at the upstream gauging station described in the permit.

Actual Stream Dilution Ratio: To calculate the Actual Stream Dilution Ratio, divide the average upstream flow rate by the average discharge flow rate. Enter the Actual Stream Dilution Ratio accurate to the nearest 0.1.

No. of Days the SDF > Stream Dilution Ratio: For each day of discharge, compare the minimum Stream Dilution Factor (SDF) from the permit to the calculated Stream Dilution Ratio. On Part B of the DMR, enter an asterisk (*) if the SDF is greater than the Stream Dilution Ratio on any day of discharge. On Part A of the DMR, add up the days with an "*" and record the total number of days the Stream Dilution Factor was greater than the Stream

CBOD₅: Enter the average CBOD₅ of the reclaimed water discharged during the period shown in duration of discharge.

TKN: Enter the average TKN of the reclaimed water discharged during the period shown in duration of discharge.

Actual Rainfall: Enter the actual rainfall for each day on Part B. Enter the actual cumulative rainfall to date for this calendar year and the actual total monthly rainfall on Part A. The cumulative rainfall to date for this calendar year is the total amount of rain, in inches, that has been recorded since January 1 of the current year through the month for which this DMR contains data.

Rainfall During Average Rainfall Year: On Part A, enter the total monthly rainfall during the average rainfall year and the cumulative rainfall for the average rainfall year. the amount of rain, in inches, which fell during the average rainfall year from January through the month for which this DMR contains data.

No. of Days LWWD Activated During Calendar Year: Enter the cumulative number of days that the limited wet weather discharge was activated since January 1 of the current year.

Reason for Discharge: Attach to the DMR a brief explanation of the factors contributing to the need to activate the limited wet weather discharge.